


属性

| | |
|--------|------------------------|
| 接口 1 | BSP外螺纹,圆柱形 |
| 密封形式 1 | B型 |
| 接口 2 | 米制外螺纹,圆柱形 |
| 密封形式 2 | 24°内锥 |
| 结构类型 | 旋入式螺栓连接 |
| 结构形式 | 直道 |
| 标准 | DIN 2353 ISO 8434-1 |
| 供货范围 | 带锁紧螺母和切割环的接套 |
| 原料 | 黄铜 |



提示

有关安装、装入、压力负荷和允许的工作温度的说明请您参阅管螺栓连接的技术信息。

货品

| 名称 | 结构系列 | 工作压力 巴 | 管外径 Ø (mm) | G | D (mm) | i (mm) | L1 (mm) | L2 (mm) | S1 | S3 |
|--------------------|------|--------|------------|--------------|--------|--------|---------|---------|----|----|
| VR NW 04 HL MG | L | PN 200 | 6 | G 1/8" -28 | 14 | 8 | 23,0 | 8,5 | 14 | 14 |
| VR NW 04 HL 1/4 MG | L | PN 200 | 6 | G 1/4" -19 | 18 | 12 | 24,5 | 10,0 | 19 | 14 |
| VR NW 04 HL 3/8 MG | L | PN 200 | 6 | G 3/8" -19 | 22 | 12 | 26,0 | 11,5 | 22 | 14 |
| VR NW 04 HL 1/2 MG | L | PN 200 | 6 | G 1/2" -14 | 26 | 14 | 26,5 | 12,0 | 27 | 14 |
| VR NW 06 HL 1/8 MG | L | PN 200 | 8 | G 1/8" -28 | 14 | 8 | 24,0 | 9,0 | 14 | 17 |
| VR NW 06 HL MG | L | PN 200 | 8 | G 1/4" -19 | 18 | 12 | 25,0 | 10,0 | 19 | 17 |
| VR NW 06 HL 3/8 MG | L | PN 200 | 8 | G 3/8" -19 | 22 | 12 | 26,5 | 11,5 | 22 | 17 |
| VR NW 06 HL 1/2 MG | L | PN 200 | 8 | G 1/2" -14 | 26 | 14 | 27,0 | 12,0 | 27 | 17 |
| VR NW 08 HL MG | L | PN 200 | 10 | G 1/4" -19 | 18 | 12 | 26,0 | 11,0 | 19 | 19 |
| VR NW 08 HL 3/8 MG | L | PN 200 | 10 | G 3/8" -19 | 22 | 12 | 27,5 | 12,5 | 22 | 19 |
| VR NW 08 HL 1/2 MG | L | PN 200 | 10 | G 1/2" -14 | 26 | 14 | 28,0 | 13,0 | 27 | 19 |
| VR NW 10 HL 1/4 MG | L | PN 200 | 12 | G 1/4" -19 | 18 | 12 | 26,5 | 12,0 | 19 | 22 |
| VR NW 10 HL MG | L | PN 200 | 12 | G 3/8" -19 | 22 | 12 | 27,0 | 12,5 | 22 | 22 |
| VR NW 10 HL 1/2 MG | L | PN 200 | 12 | G 1/2" -14 | 26 | 14 | 27,5 | 13,0 | 27 | 22 |
| VR NW 13 HL 3/8 MG | L | PN 160 | 15 | G 3/8" -19 | 22 | 12 | 29,0 | 14,0 | 24 | 27 |
| VR NW 13 HL MG | L | PN 160 | 15 | G 1/2" -14 | 26 | 14 | 29,0 | 14,0 | 27 | 27 |
| VR NW 16 HL MG | L | PN 160 | 18 | G 1/2" -14 | 26 | 14 | 31,0 | 14,5 | 27 | 32 |
| VR NW 20 HL 1/2 MG | L | PN 100 | 22 | G 1/2" -14 | 26 | 14 | 33,0 | 16,5 | 32 | 36 |
| VR NW 20 HL MG | L | PN 100 | 22 | G 3/4" -14 | 32 | 16 | 33,0 | 16,5 | 32 | 36 |
| VR NW 25 HL MG | L | PN 100 | 28 | G 1" -11 | 39 | 18 | 34,0 | 17,5 | 41 | 41 |
| VR NW 32 HL MG | L | PN 100 | 35 | G 1.1/4" -11 | 49 | 20 | 39,0 | 17,5 | 50 | 50 |
| VR NW 40 HL MG | L | PN 100 | 42 | G 1.1/2" -11 | 55 | 22 | 42,0 | 19,0 | 55 | 60 |
| VR NW 03 HS MG | S | PN 250 | 6 | G 1/4" -19 | 18 | 12 | 28,0 | 13,0 | 19 | 17 |
| VR NW 04 HS MG | S | PN 250 | 8 | G 1/4" -19 | 18 | 12 | 30,0 | 15,0 | 19 | 19 |
| VR NW 04 HS 1/2 MG | S | PN 250 | 8 | G 1/2" -14 | 26 | 14 | 34,0 | 17,5 | 27 | 19 |
| VR NW 06 HS 1/4 MG | S | PN 250 | 10 | G 1/4" -19 | 18 | 12 | 30,5 | 14,5 | 22 | 22 |
| VR NW 06 HS MG | S | PN 250 | 10 | G 3/8" -19 | 22 | 12 | 31,0 | 15,0 | 22 | 22 |
| VR NW 06 HS 1/2 MG | S | PN 250 | 10 | G 1/2" -14 | 26 | 14 | 33,5 | 17,5 | 27 | 22 |
| VR NW 08 HS MG | S | PN 250 | 12 | G 3/8" -19 | 22 | 12 | 33,0 | 17,0 | 22 | 24 |
| VR NW 08 HS 1/2 MG | S | PN 250 | 12 | G 1/2" -14 | 26 | 14 | 33,5 | 17,5 | 27 | 24 |
| VR NW 10 HS MG | S | PN 250 | 14 | G 1/2" -14 | 26 | 14 | 37,0 | 19,0 | 27 | 27 |
| VR NW 13 HS MG | S | PN 250 | 16 | G 1/2" -14 | 26 | 14 | 37,0 | 18,5 | 27 | 30 |
| VR NW 16 HS 1/2 MG | S | PN 250 | 20 | G 1/2" -14 | 26 | 14 | 44,0 | 22,5 | 32 | 36 |
| VR NW 16 HS MG | S | PN 250 | 20 | G 3/4" -14 | 39 | 18 | 44,0 | 22,5 | 32 | 36 |
| VR NW 20 HS 3/4 MG | S | PN 160 | 25 | G 3/4" -14 | 32 | 16 | 47,0 | 23,0 | 41 | 46 |
| VR NW 20 HS MG | S | PN 160 | 25 | G 1" -11 | 39 | 18 | 47,0 | 23,0 | 41 | 46 |
| VR NW 25 HS MG | S | PN 100 | 30 | G 1.1/4" -11 | 49 | 20 | 50,0 | 23,5 | 50 | 50 |
| VR NW 32 HS MG | S | PN 100 | 38 | G 1.1/2" -11 | 55 | 22 | 57,0 | 26,0 | 55 | 60 |

结构系列: LL=非常轻 L=轻 S=重 - PN = 额定压力 PB = 最大工作压力 - Ø = 管外径

产品变体

| | |
|-------|--------------|
| VR | 旋入式螺栓连接, 钢 |
| VR VA | 旋入式螺栓连接, 不锈钢 |