

属性

接口 1	NPT内螺纹
密封形式 1	螺纹密封式
接口 2	米制外螺纹,圆柱形
密封形式 2	24°内锥
结构类型	旋上式螺栓连接
结构形式	直道
供货范围	接套(不带锁紧螺母和切割环)
原料	不锈钢



提示

有关安装、装入、压力负荷和允许的工作温度的说明请您参阅管螺栓连接的技术信息。

货品

名称	结构系列	工作压力 巴	Ø d2 (mm)	G1	G2	i (mm)	L1 (mm)	L2 (mm)	SW (mm)
XGAN NW 04 HL VA	L	PN 315	6	1/8" -27 NPT	M 12 x 1.5	11,6	26,0	19,0	14
XGAN NW 04 HL 1/4 VA	L	PN 315	6	1/4" -18 NPT	M 12 x 1.5	16,4	30,5	23,5	19
XGAN NW 06 HL VA	L	PN 315	8	1/4" -18 NPT	M 14 x 1.5	16,4	30,5	23,5	19
XGAN NW 08 HL VA	L	PN 315	10	1/4" -18 NPT	M 16 x 1.5	16,4	31,0	24,0	19
XGAN NW 08 HL 1/2 VA	L	PN 315	10	1/2" -14 NPT	M 16 x 1.5	22,6	39,0	32,0	27
XGAN NW 10 HL 1/4 VA	L	PN 315	12	1/4" -18 NPT	M 18 x 1.5	16,4	31,0	24,0	19
XGAN NW 10 HL VA	L	PN 315	12	3/8" -18 NPT	M 18 x 1.5	17,4	34,0	27,0	24
XGAN NW 10 HL 1/2 VA	L	PN 315	12	1/2" -14 NPT	M 18 x 1.5	22,6	39,0	32,0	27
XGAN NW 13 HL VA	L	PN 315	15	1/2" -14 NPT	M 22 x 1.5	22,6	40,0	33,0	27
XGAN NW 16 HL VA	L	PN 315	18	1/2" -14 NPT	M 26 x 1.5	22,6	40,0	32,5	27
XGAN NW 20 HL VA	L	PN 160	22	3/4" -14 NPT	M 30 x 2	23,1	43,0	35,5	36
XGAN NW 25 HL VA	L	PN 160	28	1" -11.5 NPT	M 36 x 2	27,8	48,0	40,5	41
XGAN NW 32 HL VA	L	PN 160	35	1.1/4" -11.5 NPT	M 45 x 2	28,3	51,0	40,5	55
XGAN NW 40 HL VA	L	PN 160	42	1.1/2" -11.5 NPT	M 52 x 2	28,3	53,0	42,0	60
XGAN NW 03 HS VA	S	PN 630	6	1/4" -18 NPT	M 14 x 1.5	16,4	33,0	26,0	19
XGAN NW 04 HS VA	S	PN 630	8	1/4" -18 NPT	M 16 x 1.5	16,4	33,0	26,0	19
XGAN NW 06 HS VA	S	PN 630	10	3/8" -18 NPT	M 18 x 1.5	17,4	35,0	27,0	24
XGAN NW 08 HS VA	S	PN 630	12	3/8" -18 NPT	M 20 x 1.5	17,4	35,0	27,5	24
XGAN NW 08 HS 1/2 VA	S	PN 630	12	1/2" -14 NPT	M 20 x 1.5	22,6	41,0	33,5	27
XGAN NW 10 HS VA	S	PN 630	14	1/2" -14 NPT	M 22 x 1.5	22,6	43,0	35,0	27
XGAN NW 13 HS VA	S	PN 400	16	1/2" -14 NPT	M 24 x 1.5	22,6	43,0	34,5	27
XGAN NW 16 HS VA	S	PN 400	20	3/4" -14 NPT	M 30 x 2	23,1	46,0	35,5	36
XGAN NW 20 HS VA	S	PN 400	25	1" -11.5 NPT	M 36 x 2	27,8	53,0	41,0	41
XGAN NW 25 HS VA	S	PN 400	30	1.1/4" -11.5 NPT	M 42 x 2	28,3	57,0	43,5	55
XGAN NW 32 HS VA	S	PN 315	38	1.1/2" -11.5 NPT	M 52 x 2	28,3	59,0	43,0	60

结构系列:LL=非常轻 L=轻 S=重 - PN = 额定压力 PB = 最大工作压力 - Ø d2 = 管外直径

产品变体

XGAN VA 旋上式螺栓连接,带锁紧螺母和切割环的接套