


属性

| | |
|--------|------------------------|
| 接口 1 | BSPT外螺纹,圆锥形 |
| 密封形式 1 | 螺纹密封式 |
| 接口 2 | 米制外螺纹,圆柱形 |
| 密封形式 2 | 24°内锥 |
| 结构类型 | 旋入式螺栓连接 |
| 结构形式 | 直道 |
| 标准 | DIN 2353 ISO 8434-1 |
| 供货范围 | 接套(不带锁紧螺母和切割环) |
| 原料 | 钢 |
| 表面保护 | 电镀涂层 |



提示

有关安装、装入、压力负荷和允许的工作温度的说明请您参阅管螺栓连接的技术信息。

货品

| 名称 | 结构系列 | 工作压力 巴 | Ø d2 (mm) | G | i (mm) | L2 (mm) | L7 (mm) | SW (mm) |
|-------------------|------|--------|-----------|------------|--------|---------|---------|---------|
| XVR 04 LL | LL | PN 100 | 4 | R 1/8" K | 8,0 | 16,0 | 20,0 | 11 |
| XVR 05 LL | LL | PN 100 | 5 | R 1/8" K | 8,0 | 14,5 | 20,0 | 11 |
| XVR 06 LL | LL | PN 100 | 6 | R 1/8" K | 8,0 | 14,5 | 20,0 | 11 |
| XVR 06 LL 1/4 | LL | PN 100 | 6 | R 1/4" K | 12,0 | 14,5 | 20,0 | 12 |
| XVR 08 LL | LL | PN 100 | 8 | R 1/8" K | 8,0 | 16,5 | 22,0 | 12 |
| XVR 08 LL 1/4 | LL | PN 100 | 8 | R 1/4" K | 12,0 | 20,5 | 26,0 | 14 |
| XVR 10 LL | LL | PN 100 | 10 | R 1/4" K | 12,0 | 20,5 | 26,0 | 14 |
| XVR 12 LL | LL | PN 100 | 12 | R 1/4" K | 12,0 | 20,0 | 26,0 | 17 |
| XVR 12 LL 3/8 | LL | PN 100 | 12 | R 3/8" K | 12,0 | 20,0 | 26,0 | 17 |
| XVRK NW 04 HL | L | PN 315 | 6 | R 1/8" K | 10,5 | 17,5 | 24,5 | 12 |
| XVRK NW 04 HL 1/4 | L | PN 315 | 6 | R 1/4" K | 14,0 | 22,0 | 29,0 | 17 |
| XVRK NW 06 HL 1/8 | L | PN 315 | 8 | R 1/8" K | 10,5 | 18,5 | 25,5 | 14 |
| XVRK NW 06 HL | L | PN 315 | 8 | R 1/4" K | 14,0 | 22,0 | 29,0 | 17 |
| XVRK NW 06 HL 3/8 | L | PN 315 | 8 | R 3/8" K | 14,5 | 22,5 | 30,5 | 19 |
| XVRK NW 06 HL 1/2 | L | PN 315 | 8 | R 1/2" K | 18,5 | 27,5 | 34,5 | 22 |
| XVRK NW 08 HL 1/8 | L | PN 315 | 10 | R 1/8" K | 10,5 | 19,5 | 26,5 | 17 |
| XVRK NW 08 HL | L | PN 315 | 10 | R 1/4" K | 14,0 | 23,0 | 30,0 | 17 |
| XVRK NW 08 HL 3/8 | L | PN 315 | 10 | R 3/8" K | 14,5 | 24,5 | 31,5 | 19 |
| XVRK NW 08 HL 1/2 | L | PN 315 | 10 | R 1/2" K | 18,5 | 28,5 | 35,5 | 22 |
| XVRK NW 10 HL 1/4 | L | PN 315 | 12 | R 1/4" K | 14,0 | 24,0 | 31,0 | 19 |
| XVRK NW 10 HL | L | PN 315 | 12 | R 3/8" K | 14,5 | 24,5 | 31,5 | 19 |
| XVRK NW 10 HL 1/2 | L | PN 315 | 12 | R 1/2" K | 18,5 | 28,5 | 35,5 | 24 |
| XVRK NW 13 HL 3/8 | L | PN 315 | 15 | R 3/8" K | 14,5 | 25,5 | 24,0 | 33 |
| XVRK NW 13 HL | L | PN 315 | 15 | R 1/2" K | 18,5 | 29,5 | 36,5 | 24 |
| XVRK NW 16 HL 3/8 | L | PN 315 | 18 | R 3/8" K | 14,5 | 26,0 | 33,5 | 27 |
| XVRK NW 16 HL | L | PN 315 | 18 | R 1/2" K | 18,5 | 30,0 | 37,5 | 27 |
| XVRK NW 16 HL 3/4 | L | PN 160 | 18 | R 3/4" K | 20,0 | 31,5 | 39,0 | 32 |
| XVRK NW 20 HL 1/2 | L | PN 160 | 22 | R 1/2" K | 18,5 | 32,0 | 39,5 | 32 |
| XVRK NW 20 HL | L | PN 160 | 22 | R 3/4" K | 20,0 | 33,5 | 41,0 | 32 |
| XVRK NW 25 HL | L | PN 160 | 28 | R 1" K | 24,0 | 38,5 | 46,0 | 41 |
| XVRK NW 32 HL 1 | L | PN 160 | 35 | R 1" K | 24,0 | 40,5 | 51,0 | 46 |
| XVRK NW 32 HL | L | PN 160 | 35 | R 1.1/4" K | 26,0 | 42,5 | 53,0 | 46 |
| XVRK NW 40 HL | L | PN 160 | 42 | R 1.1/2" K | 27,0 | 43,0 | 54,0 | 55 |
| XVRK NW 03 HS | S | PN 400 | 6 | R 1/4" K | 14,0 | 27,0 | 34,0 | 17 |
| XVRK NW 04 HS | S | PN 400 | 8 | R 1/4" K | 14,0 | 27,0 | 34,0 | 17 |
| XVRK NW 06 HS 1/4 | S | PN 400 | 10 | R 1/4" K | 14,0 | 26,5 | 34,0 | 19 |
| XVRK NW 06 HS | S | PN 400 | 10 | R 3/8" K | 14,5 | 27,0 | 34,5 | 19 |
| XVRK NW 08 HS 1/4 | S | PN 400 | 12 | R 1/4" K | 14,0 | 28,5 | 36,0 | 22 |
| XVRK NW 08 HS | S | PN 400 | 12 | R 3/8" K | 14,5 | 29,0 | 36,5 | 22 |
| XVRK NW 08 HS 1/2 | S | PN 400 | 12 | R 1/2" K | 18,5 | 33,0 | 40,5 | 22 |
| XVRK NW 10 HS 3/8 | S | PN 400 | 14 | R 3/8" K | 14,5 | 30,5 | 38,5 | 24 |



货品

| 名称 | 结构系列 | 工作压力 巴 | Ø d2 (mm) | G | i (mm) | L2 (mm) | L7 (mm) | SW (mm) |
|-------------------|------|--------|--------------|------------|-----------|------------|------------|------------|
| XVRK NW 10 HS | S | PN 400 | 14 | R 1/2" K | 18,5 | 34,5 | 42,5 | 24 |
| XVRK NW 13 HS 3/8 | S | PN 400 | 16 | R 3/8" K | 14,5 | 30,0 | 38,5 | 27 |
| XVRK NW 13 HS | S | PN 400 | 16 | R 1/2" K | 18,5 | 34,0 | 42,5 | 27 |
| XVRK NW 16 HS | S | PN 400 | 20 | R 3/4" K | 20,0 | 37,5 | 48,0 | 32 |
| XVRK NW 20 HS | S | PN 400 | 25 | R 1" K | 24,0 | 43,0 | 55,0 | 41 |
| XVRK NW 25 HS 1 | S | PN 400 | 30 | R 1" K | 24,0 | 43,5 | 57,0 | 46 |
| XVRK NW 25 HS | S | PN 400 | 30 | R 1.1/4" K | 26,0 | 45,5 | 59,0 | 46 |
| XVRK NW 32 HS | S | PN 315 | 38 | R 1.1/2" K | 27,0 | 49,0 | 65,0 | 55 |

结构系列: LL=非常轻 L=轻 S=重 - PN = 额定压力 PB = 最大工作压力 - Ø d2 = 管外直径

产品变体

| | |
|---------|--------------|
| XVRK VA | 旋入式螺栓连接, 不锈钢 |
| VRK | 旋入式螺栓连接, 钢 |