


AFS S U (3000 / 6000 PSI)

SAE焊入式法兰

HANSA FLEX

属性

| | |
|------|-------------------------|
| 标准 | SAE J 518 C ISO 6162 |
| 结构形式 | 直道 |
| 结构类型 | SAE焊入式法兰 |
| 固定 | 螺钉钻孔 |
| 供货范围 | 带UNC标准螺钉组件和O形圈 |
| 原料 | S355J2G3 (ST52.3) |
| 表面保护 | 经黑色润滑油处理 |



提示

给出的最大工作压力针对的是法兰!实际工作压力视管(壁厚)和管的品质而定!

货品

| 名称 | 压力系列 | PB 10.9 (bar) | 结构尺 寸 | A (mm) | Ø B (mm) | C (mm) | D (mm) | E (mm) | F (mm) | G (mm) | H (mm) | I (mm) | L (mm) | M unc |
|-----------------|----------|------------------|----------|-----------|-------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|----------------|
| AFS 80 S U | 3000 PSI | 350 | 1/2" | 21,6 | 13 | 38,1 | 54 | 17,5 | 46 | 36 | 16 | 19 | 9,0 | 5/16" x 1.1/4" |
| AFS 80 S U 3/8 | 3000 PSI | 350 | 1/2" | 17,5 | 13 | 38,1 | 54 | 17,5 | 46 | 36 | 16 | 19 | 9,0 | 5/16" x 1.1/4" |
| AFS 80 S U A20 | 3000 PSI | 350 | 1/2" | 20,3 | 13 | 38,1 | 54 | 17,5 | 46 | 36 | 16 | 19 | 9,0 | 5/16" x 1.1/4" |
| AFS 100 S U | 3000 PSI | 350 | 3/4" | 27,2 | 19 | 47,6 | 65 | 22,2 | 50 | 36 | 18 | 19 | 11,0 | 3/8" x 1.1/2" |
| AFS 100 S U A25 | 3000 PSI | 350 | 3/4" | 25,3 | 19 | 47,6 | 65 | 22,2 | 50 | 36 | 18 | 19 | 11,0 | 3/8" x 1.1/2" |
| AFS 102 S U | 3000 PSI | 315 | 1" | 34,0 | 25 | 52,4 | 70 | 26,2 | 55 | 38 | 18 | 19 | 11,0 | 3/8" x 1.1/2" |
| AFS 102 S U A30 | 3000 PSI | 315 | 1" | 30,3 | 25 | 52,4 | 70 | 26,2 | 55 | 38 | 18 | 19 | 11,0 | 3/8" x 1.1/2" |
| AFS 104 S U | 3000 PSI | 250 | 1.1/4" | 42,8 | 32 | 58,7 | 79 | 30,2 | 68 | 41 | 21 | 22 | 11,5 | 7/16" x 1.1/2" |
| AFS 104 S U A38 | 3000 PSI | 250 | 1.1/4" | 38,3 | 32 | 58,7 | 79 | 30,2 | 68 | 41 | 21 | 22 | 11,5 | 7/16" x 1.1/2" |
| AFS 106 S U | 3000 PSI | 200 | 1.1/2" | 48,6 | 38 | 69,9 | 93 | 35,7 | 78 | 45 | 25 | 24 | 13,5 | 1/2" x 1.3/4" |
| AFS 106 S U A50 | 3000 PSI | 200 | 1.1/2" | 50,5 | 38 | 69,9 | 93 | 35,7 | 78 | 45 | 25 | 24 | 13,5 | 1/2" x 1.3/4" |
| AFS 108 S U | 3000 PSI | 200 | 2" | 61,0 | 51 | 77,8 | 102 | 42,9 | 90 | 45 | 25 | 26 | 13,5 | 1/2" x 1.3/4" |
| AFS 110 S U | 3000 PSI | 160 | 2.1/2" | 76,6 | 63 | 88,9 | 114 | 50,8 | 105 | 50 | 25 | 30 | 13,5 | 1/2" x 1.3/4" |
| AFS 112 S U | 3000 PSI | 138 | 3" | 90,5 | 73 | 106,4 | 134 | 61,9 | 124 | 50 | 27 | 34 | 17,5 | 5/8" x 2" |
| AFS 114 S U | 3000 PSI | 35 | 3.1/2" | 103,0 | 89 | 120,7 | 152 | 69,9 | 136 | 48 | 27 | 34 | 17,5 | 5/8" x 2" |
| AFS 116 S U | 3000 PSI | 35 | 4" | 115,1 | 99 | 130,2 | 162 | 77,8 | 146 | 48 | 27 | 34 | 17,5 | 5/8" x 2" |
| AFS 401 S U | 6000 PSI | 400 | 1/2" | 21,6 | 13 | 40,5 | 54 | 18,2 | 46 | 36 | 16 | 19 | 9,0 | 5/16" x 1.1/4" |
| AFS 401 S U 3/8 | 6000 PSI | 400 | 1/2" | 17,5 | 13 | 40,5 | 54 | 18,2 | 46 | 36 | 16 | 19 | 9,0 | 5/16" x 1.1/4" |
| AFS 401 S U A20 | 6000 PSI | 400 | 1/2" | 20,3 | 13 | 40,5 | 54 | 18,2 | 46 | 36 | 16 | 19 | 9,0 | 5/16" x 1.1/4" |
| AFS 402 S U | 6000 PSI | 400 | 3/4" | 27,2 | 19 | 50,8 | 71 | 23,8 | 55 | 35 | 21 | 22 | 11,0 | 3/8" x 1.1/2" |
| AFS 402 S U A25 | 6000 PSI | 400 | 3/4" | 25,3 | 19 | 50,8 | 71 | 23,8 | 55 | 35 | 21 | 22 | 11,0 | 3/8" x 1.1/2" |
| AFS 403 S U | 6000 PSI | 400 | 1" | 34,0 | 25 | 57,2 | 81 | 27,8 | 65 | 42 | 25 | 22 | 13,0 | 7/16" x 1.3/4" |
| AFS 403 S U A30 | 6000 PSI | 400 | 1" | 30,3 | 25 | 57,2 | 81 | 27,8 | 65 | 42 | 25 | 22 | 13,0 | 7/16" x 1.3/4" |
| AFS 404 S U | 6000 PSI | 400 | 1.1/4" | 42,8 | 32 | 66,7 | 95 | 31,8 | 78 | 45 | 27 | 25 | 13,5 | 1/2" x 1.3/4" |
| AFS 404 S U A38 | 6000 PSI | 400 | 1.1/4" | 38,3 | 32 | 66,7 | 95 | 31,8 | 78 | 45 | 27 | 25 | 13,5 | 1/2" x 1.3/4" |
| AFS 405 S U | 6000 PSI | 400 | 1.1/2" | 48,6 | 38 | 79,4 | 112 | 36,5 | 94 | 50 | 30 | 28 | 17,5 | 5/8" x 2" |
| AFS 405 S U A50 | 6000 PSI | 400 | 1.1/2" | 50,5 | 38 | 79,4 | 112 | 36,5 | 94 | 50 | 30 | 28 | 17,5 | 5/8" x 2" |
| AFS 406 S U | 6000 PSI | 400 | 2" | 61,0 | 51 | 96,8 | 134 | 44,5 | 114 | 65 | 37 | 24 | 21,0 | 3/4" x 2.1/2" |

PN = 额定压力 PB = 最大工作压力

产品变体

| | |
|---------------------------|-----------------------|
| AFS S (3000 PSI) | SAE焊入式法兰, 仅法兰 |
| AFS S M (3000 / 6000 PSI) | SAE焊入式法兰, 带米制螺钉组件和O形圈 |