


属性	
结构类型	泵接口(4孔)
结构形式	直道
固定	带米制螺钉组件
供货范围	带螺钉组件和O形圈
原料	钢 ST 42.3
表面保护	电镀涂层





提示

给出的最大工作压力针对的是法兰!实际工作压力视管(壁厚)和管的品质而定!

压力 PB (bar)	LK (mm)	A	ØB (mm)	D (mm)	G (mm)	H (mm)	L (mm)	螺钉	OR
250	30	G 1/2" -14	14	45	55	10	6,5	(4 x) M 6 x 20	18.77 x 1.78
250	40	G 3/4" -14	19	58	60	12	8,5	(4 x) M 8 x 25	25.12 x 1.78
250	51	G 1" -11	24	76	72	16	10,5	(4 x) M 10 x 30	31.42 x 2.62
250	56	G 1" -11	24	76	72	16	10,5	(4 x) M 10 x 30	31.42 x 2.62
	(bar) 250 250 250	(bar) (mm) 250 30 250 40 250 51	(bar) (mm) 250 30 G 1/2" -14 250 40 G 3/4" -14 250 51 G 1" -11	(bar) (mm) (mm) 250 30 G 1/2" -14 14 250 40 G 3/4" -14 19 250 51 G 1" -11 24	(bar) (mm) (mm) (mm) 250 30 G 1/2" -14 14 45 250 40 G 3/4" -14 19 58 250 51 G 1" -11 24 76	(bar) (mm) (mm) (mm) (mm) 250 30 G 1/2" -14 14 45 55 250 40 G 3/4" -14 19 58 60 250 51 G 1" -11 24 76 72	(bar) (mm) (mm) (mm) (mm) (mm) 250 30 G 1/2" -14 14 45 55 10 250 40 G 3/4" -14 19 58 60 12 250 51 G 1" -11 24 76 72 16	(bar) (mm) <t< td=""><td>(bar) (mm) (mm) (mm) (mm) (mm) (mm) 250 30 G 1/2" -14 14 45 55 10 6,5 (4 x) M 6 x 20 250 40 G 3/4" -14 19 58 60 12 8,5 (4 x) M 8 x 25 250 51 G 1" -11 24 76 72 16 10,5 (4 x) M 10 x 30</td></t<>	(bar) (mm) (mm) (mm) (mm) (mm) (mm) 250 30 G 1/2" -14 14 45 55 10 6,5 (4 x) M 6 x 20 250 40 G 3/4" -14 19 58 60 12 8,5 (4 x) M 8 x 25 250 51 G 1" -11 24 76 72 16 10,5 (4 x) M 10 x 30

PN = 额定压力 PB = 最大工作压力