


GFS N U (3000 / 6000 PSI)

SAE旋入式对接法兰,NPT

HANSA FLEX

属性

| | |
|------|-------------------------|
| 标准 | SAE J 518 C ISO 6162 |
| 结构形式 | 直道 |
| 结构类型 | SAE旋入式对接法兰 |
| 固定 | UNC标准螺钉用内螺纹 |
| 供货范围 | 仅法兰 |
| 原料 | S355J2G3 (ST52.3) |
| 表面保护 | 经黑色润滑油处理 |



提示

给出的最大工作压力针对的是法兰!实际工作压力视管(壁厚)和管的品质而定!

货品

| 名称 | 压力系列 | PB 10.9 (bar) | 结构尺寸 | A | Ø B (mm) | C (mm) | D (mm) | E (mm) | F (mm) | G (mm) | H (mm) | I (mm) | M unc |
|-------------------|----------|------------------|--------|------------------|-------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-------|
| GFS 80 N U | 3000 PSI | 350 | 1/2" | NPT 1/2" -14 | 13 | 38,1 | 54 | 17,5 | 46 | 36 | 16 | 19 | 5/16" |
| GFS 80 N 3/8 U | 3000 PSI | 350 | 1/2" | NPT 3/8" -18 | 13 | 38,1 | 54 | 17,5 | 46 | 36 | 16 | 19 | 5/16" |
| GFS 100 N U | 3000 PSI | 350 | 3/4" | NPT 3/4" -14 | 19 | 47,6 | 65 | 22,2 | 50 | 36 | 18 | 19 | 3/8" |
| GFS 100 N 1/2 U | 3000 PSI | 350 | 3/4" | NPT 1/2" -14 | 13 | 47,6 | 65 | 22,2 | 50 | 36 | 18 | 19 | 3/8" |
| GFS 102 N U | 3000 PSI | 315 | 1" | NPT 1" -11.5 | 25 | 52,4 | 70 | 26,2 | 55 | 38 | 18 | 22 | 3/8" |
| GFS 102 N 3/4 U | 3000 PSI | 315 | 1" | NPT 3/4" -14 | 19 | 52,4 | 70 | 26,2 | 55 | 35 | 21 | 19 | 3/8" |
| GFS 104 N U | 3000 PSI | 250 | 1.1/4" | NPT 1.1/4" -11.5 | 32 | 58,7 | 79 | 30,2 | 68 | 41 | 21 | 22 | 7/16" |
| GFS 104 N 1 U | 3000 PSI | 250 | 1.1/4" | NPT 1" -11.5 | 25 | 58,7 | 81 | 30,2 | 65 | 42 | 25 | 22 | 7/16" |
| GFS 106 N U | 3000 PSI | 200 | 1.1/2" | NPT 1.1/2" | 38 | 69,9 | 93 | 35,7 | 78 | 45 | 25 | 24 | 1/2" |
| GFS 106 N 1 1/4 U | 3000 PSI | 200 | 1.1/2" | NPT 1.1/4" -11.5 | 32 | 69,9 | 95 | 35,7 | 78 | 45 | 27 | 24 | 1/2" |
| GFS 108 N U | 3000 PSI | 200 | 2" | NPT 2" -11.5 | 51 | 77,8 | 102 | 42,9 | 90 | 45 | 25 | 30 | 1/2" |
| GFS 108 N 1 1/2 U | 3000 PSI | 200 | 2" | NPT 1.1/2" | 38 | 77,8 | 102 | 42,9 | 90 | 45 | 25 | 26 | 1/2" |
| GFS 110 N U | 3000 PSI | 160 | 2.1/2" | NPT 2.1/2" -11.5 | 63 | 88,9 | 114 | 50,8 | 105 | 50 | 25 | 30 | 1/2" |
| GFS 112 N U | 3000 PSI | 138 | 3" | NPT 3" -11.5 | 73 | 106,4 | 134 | 61,9 | 124 | 50 | 27 | 34 | 5/8" |
| GFS 114 N U | 3000 PSI | 35 | 3.1/2" | NPT 3.1/2" -11.5 | 89 | 120,7 | 152 | 69,9 | 136 | 48 | 27 | 34 | 5/8" |
| GFS 116 N U | 3000 PSI | 35 | 4" | NPT 4" -11.5 | 99 | 130,2 | 162 | 77,8 | 146 | 48 | 27 | 34 | 5/8" |
| GFS 401 N U | 6000 PSI | 400 | 1/2" | NPT 1/2" -14 | 13 | 40,5 | 54 | 18,2 | 46 | 36 | 16 | 19 | 5/16" |
| GFS 401 N 3/8 U | 6000 PSI | 400 | 1/2" | NPT 3/8" -18 | 13 | 40,5 | 54 | 18,2 | 46 | 36 | 16 | 19 | 5/16" |
| GFS 402 N U | 6000 PSI | 400 | 3/4" | NPT 3/4" -14 | 19 | 50,8 | 71 | 23,8 | 55 | 35 | 21 | 22 | 3/8" |
| GFS 402 N 1/2 U | 6000 PSI | 400 | 3/4" | NPT 1/2" -14 | 13 | 50,8 | 71 | 23,8 | 55 | 35 | 21 | 22 | 3/8" |
| GFS 403 N U | 6000 PSI | 400 | 1" | NPT 1" -11.5 | 25 | 57,2 | 81 | 27,8 | 65 | 42 | 25 | 24 | 7/16" |
| GFS 403 N 3/4 U | 6000 PSI | 400 | 1" | NPT 3/4" -14 | 19 | 57,2 | 81 | 27,8 | 65 | 42 | 25 | 24 | 7/16" |
| GFS 404 N U | 6000 PSI | 400 | 1.1/4" | NPT 1.1/4" -11.5 | 32 | 66,7 | 95 | 31,8 | 78 | 45 | 27 | 25 | 1/2" |
| GFS 404 N 1 U | 6000 PSI | 400 | 1.1/4" | NPT 1" -11.5 | 25 | 66,7 | 95 | 31,8 | 78 | 45 | 27 | 25 | 1/2" |
| GFS 405 N U | 6000 PSI | 400 | 1.1/2" | NPT 1.1/2" | 38 | 79,4 | 112 | 36,5 | 94 | 50 | 30 | 28 | 5/8" |
| GFS 405 N 1 1/4 U | 6000 PSI | 400 | 1.1/2" | NPT 1.1/4" -11.5 | 32 | 79,4 | 112 | 36,5 | 94 | 50 | 30 | 28 | 5/8" |
| GFS 406 N U | 6000 PSI | 400 | 2" | NPT 2" -11.5 | 51 | 96,8 | 134 | 44,5 | 114 | 65 | 37 | 30 | 3/4" |
| GFS 406 N 1 1/2 U | 6000 PSI | 400 | 2" | NPT 1.1/2" | 38 | 96,8 | 134 | 44,5 | 114 | 65 | 37 | 30 | 3/4" |

PN = 额定压力 PB = 最大工作压力

产品变体

GFS N M (3000 / 6000 PSI) SAE旋入式对接法兰,NPT, 仅法兰