


# WF LK M

泵接口,(4孔),角度90°

**HANSA FLEX**

## 属性

结构类型	泵接口(4孔)
结构形式	角度90°
标准	DIN 3901 / 3902
固定	带米制螺钉组件
供货范围	带螺钉组件、O形圈、螺母和切割环
原料	韧性铸铁 GTW40
表面保护	电镀涂层



## 货品

名称	结构系列	I (mm)	Ø RAD (mm)	压力 PB (bar)	A	LK	D	S1	S2	S3	L	螺钉 1	螺钉 2	OR
WF 35 LK L 10 315 M	L	14,0	10	315	M16x1,5	35	39	16,5	30,5	47,0	6,4	(2x) M 6 x 22	(2x) M 6 x 35	20.0 x 2.5
WF 35 LK L 12 315 M	L	14,0	12	315	M18x1,5	35	39	16,5	30,5	47,0	6,4	(2x) M 6 x 22	(2x) M 6 x 35	20.0 x 2.5
WF 35 LK L 15 250 M	L	14,0	15	250	M22x1,5	35	39	16,5	30,0	46,0	6,4	(2x) M 6 x 22	(2x) M 6 x 35	20.0 x 2.5
WF 35 LK L 18 250 M	L	15,0	18	250	M26x1,5	35	39	20,0	30,0	47,5	6,4	(2x) M 6 x 22	(2x) M 6 x 40	20.0 x 2.5
WF 40 LK L 15 100 M	L	20,0	15	100	M22x1,5	40	42	22,5	30,0	46,0	6,4	(2x) M 6 x 22	(2x) M 6 x 45	26.0 x 2.5
WF 40 LK L 18 100 M	L	20,0	18	100	M26x1,5	40	42	22,5	30,5	47,0	6,4	(2x) M 6 x 22	(2x) M 6 x 45	26.0 x 2.5
WF 40 LK L 22 100 M	L	20,0	22	100	M30x2	40	42	22,5	30,5	47,5	6,4	(2x) M 6 x 22	(2x) M 6 x 45	26.0 x 2.5
WF 40 LK L 28 100 M	L	20,0	28	100	M36x2	40	42	28,0	32,5	49,0	6,4	(2x) M 6 x 22	(2x) M 6 x 50	26.0 x 2.5
WF 40 LK L 35 100 M	L	20,0	35	100	M45x2	40	42	34,0	30,5	52,0	6,4	(2x) M 6 x 22	(2x) M 6 x 60	26.0 x 2.5
WF 55 LK L 35 100 M	L	26,0	35	100	M45x2	55	58	32,0	38,5	62,0	8,4	(2x) M 8 x 25	(2x) M 8 x 60	32.0 x 2.5
WF 55 LK L 42 100 M	L	26,0	42	100	M52x2	55	58	40,0	38,0	61,0	8,4	(2x) M 8 x 25	(2x) M 8 x 70	32.0 x 2.5
WF 35 LK S 16 315 M	S	15,0	16	315	M24x1,5	35	39	20,0	29,5	48,0	6,4	(2x) M 6 x 22	(2x) M 6 x 40	20.0 x 2.5
WF 35 LK S 20 315 M	S	15,0	20	315	M30x2	35	39	25,0	34,5	56,0	6,4	(2x) M 6 x 22	(2x) M 6 x 45	20.0 x 2.5
WF 40 LK S 20 250 M	S	20,0	20	250	M30x2	40	42	22,5	29,5	50,0	6,4	(2x) M 6 x 22	(2x) M 6 x 45	26.0 x 2.5
WF 55 LK S 20 250 M	S	18,0	20	250	M30x2	55	58	24,0	34,5	56,0	8,4	(2x) M 8 x 25	(2x) M 8 x 50	32.0 x 2.5
WF 55 LK S 25 250 M	S	20,0	25	250	M36x2	55	58	30,0	37,0	61,0	8,4	(2x) M 8 x 25	(2x) M 8 x 55	32.0 x 2.5
WF 55 LK S 30 250 M	S	26,0	30	250	M42x2	55	58	32,0	35,5	62,0	8,4	(2x) M 8 x 25	(2x) M 8 x 50	32.0 x 2.5

结构系列:LL=非常轻 L=轻 S=重 - PN = 额定压力 PB = 最大工作压力 - Ø RAD = 管外直径

## 产品变体

WF LK 泵接口,(4孔),角度90°,带米制螺钉组件和O形圈