

WF LK M

泵接口,(4孔),角度90°

HANSA FLEX

属性

| | |
|------|------------------|
| 结构类型 | 泵接口(4孔) |
| 结构形式 | 角度90° |
| 标准 | DIN 3901 / 3902 |
| 固定 | 带米制螺钉组件 |
| 供货范围 | 带螺钉组件、O形圈、螺母和切割环 |
| 原料 | 韧性铸铁 GTW40 |
| 表面保护 | 电镀涂层 |



货品

| 名称 | 结构系列 | I (mm) | Ø RAD (mm) | 压力 PB (bar) | A | LK (mm) | D (mm) | S1 (mm) | S2 (mm) | S3 (mm) | L (mm) | 螺钉 1 | 螺钉 2 | OR |
|---------------------|------|-----------|---------------|-------------------|---------|------------|-----------|------------|------------|------------|-----------|---------------|---------------|------------|
| WF 35 LK L 10 315 M | L | 14,0 | 10 | 315 | M16x1,5 | 35 | 39 | 16,5 | 30,5 | 47,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 35 | 20.0 x 2.5 |
| WF 35 LK L 12 315 M | L | 14,0 | 12 | 315 | M18x1,5 | 35 | 39 | 16,5 | 30,5 | 47,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 35 | 20.0 x 2.5 |
| WF 35 LK L 15 250 M | L | 14,0 | 15 | 250 | M22x1,5 | 35 | 39 | 16,5 | 30,0 | 46,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 35 | 20.0 x 2.5 |
| WF 35 LK L 18 250 M | L | 15,0 | 18 | 250 | M26x1,5 | 35 | 39 | 20,0 | 30,0 | 47,5 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 40 | 20.0 x 2.5 |
| WF 40 LK L 15 100 M | L | 20,0 | 15 | 100 | M22x1,5 | 40 | 42 | 22,5 | 30,0 | 46,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 45 | 26.0 x 2.5 |
| WF 40 LK L 18 100 M | L | 20,0 | 18 | 100 | M26x1,5 | 40 | 42 | 22,5 | 30,5 | 47,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 45 | 26.0 x 2.5 |
| WF 40 LK L 22 100 M | L | 20,0 | 22 | 100 | M30x2 | 40 | 42 | 22,5 | 30,5 | 47,5 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 45 | 26.0 x 2.5 |
| WF 40 LK L 28 100 M | L | 20,0 | 28 | 100 | M36x2 | 40 | 42 | 28,0 | 32,5 | 49,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 50 | 26.0 x 2.5 |
| WF 40 LK L 35 100 M | L | 20,0 | 35 | 100 | M45x2 | 40 | 42 | 34,0 | 30,5 | 52,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 60 | 26.0 x 2.5 |
| WF 55 LK L 35 100 M | L | 26,0 | 35 | 100 | M45x2 | 55 | 58 | 32,0 | 38,5 | 62,0 | 8,4 | (2x) M 8 x 25 | (2x) M 8 x 60 | 32.0 x 2.5 |
| WF 55 LK L 42 100 M | L | 26,0 | 42 | 100 | M52x2 | 55 | 58 | 40,0 | 38,0 | 61,0 | 8,4 | (2x) M 8 x 25 | (2x) M 8 x 70 | 32.0 x 2.5 |
| WF 35 LK S 16 315 M | S | 15,0 | 16 | 315 | M24x1,5 | 35 | 39 | 20,0 | 29,5 | 48,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 40 | 20.0 x 2.5 |
| WF 35 LK S 20 315 M | S | 15,0 | 20 | 315 | M30x2 | 35 | 39 | 25,0 | 34,5 | 56,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 45 | 20.0 x 2.5 |
| WF 40 LK S 20 250 M | S | 20,0 | 20 | 250 | M30x2 | 40 | 42 | 22,5 | 29,5 | 50,0 | 6,4 | (2x) M 6 x 22 | (2x) M 6 x 45 | 26.0 x 2.5 |
| WF 55 LK S 20 250 M | S | 18,0 | 20 | 250 | M30x2 | 55 | 58 | 24,0 | 34,5 | 56,0 | 8,4 | (2x) M 8 x 25 | (2x) M 8 x 50 | 32.0 x 2.5 |
| WF 55 LK S 25 250 M | S | 20,0 | 25 | 250 | M36x2 | 55 | 58 | 30,0 | 37,0 | 61,0 | 8,4 | (2x) M 8 x 25 | (2x) M 8 x 55 | 32.0 x 2.5 |
| WF 55 LK S 30 250 M | S | 26,0 | 30 | 250 | M42x2 | 55 | 58 | 32,0 | 35,5 | 62,0 | 8,4 | (2x) M 8 x 25 | (2x) M 8 x 50 | 32.0 x 2.5 |

结构系列:LL=非常轻 L=轻 S=重 - PN = 额定压力 PB = 最大工作压力 - Ø RAD = 管外直径

产品变体

WF LK 泵接口,(4孔),角度90°,带米制螺钉组件和O形圈