

属性

| | |
|--------|------------------------|
| 接口 1 | NPT外螺纹 |
| 密封形式 1 | 螺纹密封式 |
| 接口 2 | 米制外螺纹,圆柱形 |
| 密封形式 2 | 24°内锥 |
| 结构类型 | 旋入式螺栓连接 |
| 结构形式 | 角度90° |
| 标准 | DIN 2353 ISO 8434-1 |
| 供货范围 | 带锁紧螺母和切割环的接套 |
| 原料 | 钢 |
| 表面保护 | 电镀涂层 |



提示

有关安装、装入、压力负荷和允许的工作温度的说明请您参阅管螺栓连接的技术信息。

货品

| 名称 | 结构系列 | 工作压力 巴 | 管外径 Ø (mm) | G | i (mm) | L3 (mm) | L4 (mm) | L5 (mm) | SW (mm) | S3 |
|-----------------|------|--------|------------|------------------|--------|---------|---------|---------|---------|----|
| WN 04 LL | LL | PN 100 | 4 | 1/8" -27 NPT | 7,0 | 21 | 11,0 | 17 | 9 | 10 |
| WN 05 LL | LL | PN 100 | 5 | 1/8" -27 NPT | 8,0 | 21 | 11,0 | 18 | 11 | 10 |
| WN 06 LL | LL | PN 100 | 6 | 1/8" -27 NPT | 10,0 | 21 | 9,5 | 17 | 9 | 12 |
| WN 08 LL | LL | PN 100 | 8 | 1/8" -27 NPT | 10,0 | 21 | 9,5 | 17 | 12 | 14 |
| WN NW 04 HL | L | PN 315 | 6 | 1/8" -27 NPT | 10,0 | 27 | 12,0 | 20 | 12 | 14 |
| WN NW 04 HL 1/4 | L | PN 315 | 6 | 1/4" -18 NPT | 12,0 | 29 | 14,0 | 26 | 12 | 14 |
| WN NW 04 HL 1/2 | L | PN 315 | 6 | 1/2" -14 NPT | 17,0 | 38 | 23,0 | 34 | 19 | 14 |
| WN NW 06 HL | L | PN 315 | 8 | 1/4" -18 NPT | 12,0 | 29 | 14,0 | 26 | 12 | 17 |
| WN NW 06 HL 3/8 | L | PN 315 | 8 | 3/8" -18 NPT | 15,2 | 23 | 11,5 | 20 | 12 | 17 |
| WN NW 06 HL 1/2 | L | PN 315 | 8 | 1/2" -14 NPT | 17,5 | 30 | 15,0 | 26 | 12 | 17 |
| WN NW 08 HL | L | PN 315 | 10 | 1/4" -18 NPT | 14,0 | 30 | 15,0 | 27 | 14 | 19 |
| WN NW 08 HL 3/8 | L | PN 315 | 10 | 3/8" -18 NPT | 15,2 | 30 | 15,0 | 27 | 14 | 19 |
| WN NW 10 HL | L | PN 315 | 12 | 3/8" -18 NPT | 12,5 | 32 | 17,0 | 28 | 17 | 22 |
| WN NW 10 HL 1/4 | L | PN 315 | 12 | 1/4" -18 NPT | 14,0 | 32 | 17,0 | 28 | 17 | 22 |
| WN NW 10 HL 1/2 | L | PN 315 | 12 | 1/2" -14 NPT | 19,0 | 38 | 23,0 | 34 | 19 | 22 |
| WN NW 13 HL | L | PN 315 | 15 | 1/2" -14 NPT | 18,5 | 36 | 21,0 | 34 | 19 | 27 |
| WN NW 13 HL 3/8 | L | PN 315 | 15 | 3/8" -18 NPT | 13,0 | 36 | 21,0 | 34 | 19 | 27 |
| WN NW 16 HL | L | PN 315 | 18 | 1/2" -14 NPT | 20,0 | 40 | 23,5 | 36 | 24 | 32 |
| WN NW 16 HL 3/4 | L | PN 315 | 18 | 3/4" -14 NPT | 18,5 | 40 | 23,5 | 40 | 24 | 32 |
| WN NW 20 HL | L | PN 160 | 22 | 3/4" -14 NPT | 18,5 | 44 | 27,5 | 42 | 27 | 36 |
| WN NW 25 HL | L | PN 160 | 28 | 1" -11.5 NPT | 24,0 | 47 | 30,5 | 48 | 36 | 41 |
| WN NW 32 HL | L | PN 160 | 35 | 1.1/4" -11.5 NPT | 25,5 | 56 | 34,5 | 54 | 41 | 50 |
| WN NW 40 HL | L | PN 160 | 42 | 1.1/2" -11.5 NPT | 26,0 | 63 | 40,0 | 61 | 50 | 60 |
| WN NW 03 HS | S | PN 630 | 6 | 1/4" -18 NPT | 12,0 | 31 | 16,0 | 26 | 12 | 17 |
| WN NW 04 HS | S | PN 630 | 8 | 1/4" -18 NPT | 15,0 | 32 | 17,0 | 27 | 14 | 19 |
| WN NW 06 HS | S | PN 630 | 10 | 3/8" -18 NPT | 12,0 | 34 | 17,5 | 28 | 17 | 22 |
| WN NW 08 HS | S | PN 630 | 12 | 3/8" -18 NPT | 12,5 | 38 | 21,5 | 28 | 17 | 24 |
| WN NW 10 HS | S | PN 630 | 14 | 1/2" -14 NPT | 18,0 | 40 | 22,0 | 34 | 19 | 27 |
| WN NW 13 HS | S | PN 400 | 16 | 1/2" -14 NPT | 19,0 | 43 | 24,5 | 36 | 24 | 30 |
| WN NW 13 HS 3/4 | S | PN 400 | 16 | 3/4" -14 NPT | 20,0 | 43 | 25,0 | 40 | 24 | 30 |
| WN NW 16 HS | S | PN 400 | 20 | 3/4" -14 NPT | 20,0 | 48 | 26,6 | 42 | 27 | 36 |
| WN NW 20 HS | S | PN 400 | 25 | 1" -11.5 NPT | 24,0 | 54 | 30,0 | 48 | 36 | 46 |
| WN NW 25 HS | S | PN 400 | 30 | 1.1/4" -11.5 NPT | 25,5 | 62 | 35,5 | 54 | 41 | 50 |
| WN NW 32 HS | S | PN 315 | 38 | 1.1/2" -11.5 NPT | 26,0 | 72 | 41,0 | 61 | 50 | 60 |

PN = 额定压力 PB = 最大工作压力 - 结构系列: LL=非常轻 L=轻 S=重 - Ø = 管外径

产品变体

| | |
|-------|--------------------|
| WN MG | 旋入式螺栓连接,角度90°, 黄铜 |
| WN VA | 旋入式螺栓连接,角度90°, 不锈钢 |
| XWN | 旋入式螺栓连接,角度90°, 钢 |