


## 属性

接口 1	BSP外螺纹,圆柱形
密封形式 1	O形圈和腔环
接口 2	米制外螺纹,圆柱形
密封形式 2	24°内锥
结构类型	旋入式螺栓连接,方向可调节
结构形式	角度90°
供货范围	接套(不带锁紧螺母和切割环)
原料	钢
表面保护	电镀涂层



## 提示

有关安装、装入、压力负荷和允许的工作温度的说明请您参阅管螺栓连接的技术信息。

## 货品

名称	结构系列	工作压力巴	Ø d2 (mm)	G1	G2	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	SW (mm)	S1	OR
XEWORK 04 LL	LL	PN 250	4	G 1/8" -28	M 8 x 1	7,1	11,3	20	15	11	14	7.65 x 1.78
XEWORK 06 LL	LL	PN 250	6	G 1/8" -28	M 10 x 1	7,1	11,3	20	15	11	14	7.65 x 1.78
XEWORK NW 04 HL	L	PN 315	6	G 1/8" -28	M 12 x 1.5	7,0	14,0	19	21	14	14	7.65 x 1.78
XEWORK NW 06 HL	L	PN 315	8	G 1/4" -19	M 14 x 1.5	9,0	16,0	23	23	14	19	10.78 x 2.62
XEWORK NW 08 HL	L	PN 315	10	G 1/4" -19	M 16 x 1.5	9,0	17,0	25	24	19	19	10.77 x 2.62
XEWORK NW 10 HL	L	PN 250	12	G 3/8" -19	M 18 x 1.5	9,0	19,0	28	26	19	22	13.94 x 2.62
XEWORK NW 13 HL	L	PN 250	15	G 1/2" -14	M 22 x 1.5	13,0	21,0	30	28	22	27	17.86 x 2.62
XEWORK NW 16 HL	L	PN 250	18	G 1/2" -14	M 26 x 1.5	13,0	24,0	36	31	27	27	17.86 x 2.62
XEWORK NW 20 HL	L	PN 160	22	G 3/4" -14	M 30 x 2	13,0	28,0	36	35	30	36	23.47 x 2.62
XEWORK NW 25 HL	L	PN 160	28	G 1" -11	M 36 x 2	15,0	31,0	44	38	36	41	29.74 x 3.53
XEWORK NW 32 HL	L	PN 160	35	G 1.1/4" -11	M 45 x 2	15,0	38,0	50	48	50	50	37.69 x 3.53
XEWORK NW 40 HL	L	PN 160	42	G 1.1/2" -11	M 52 x 2	15,0	38,0	52	49	50	55	44.04 x 3.53
XEWORK NW 03 HS	S	PN 315	6	G 1/4" -19	M 14 x 1.5	9,0	15,0	23	22	14	19	10.77 x 2.62
XEWORK NW 04 HS	S	PN 315	8	G 1/4" -19	M 16 x 1.5	9,0	17,0	27	24	19	19	10.77 x 2.62
XEWORK NW 06 HS	S	PN 250	10	G 3/8" -19	M 18 x 1.5	9,0	18,0	29	25	19	22	13.94 x 2.62
XEWORK NW 08 HS	S	PN 250	12	G 3/8" -19	M 20 x 1.5	9,0	22,0	29	29	22	22	13.94 x 2.62
XEWORK NW 10 HS	S	PN 250	14	G 1/2" -14	M 22 x 1.5	13,0	25,0	36	33	27	27	18.00 x 3.00
XEWORK NW 13 HS	S	PN 250	16	G 1/2" -14	M 24 x 1.5	13,0	25,0	36	33	27	27	17.86 x 2.62
XEWORK NW 16 HS	S	PN 250	20	G 3/4" -14	M 30 x 2	12,0	28,0	39	38	30	36	23.47 x 2.62
XEWORK NW 20 HS	S	PN 250	25	G 1" -11	M 36 x 2	14,0	30,0	44	42	36	41	29.74 x 3.53
XEWORK NW 25 HS	S	PN 160	30	G 1.1/4" -11	M 42 x 2	15,0	36,0	49	49	50	50	37.69 x 3.53
XEWORK NW 32 HS	S	PN 160	38	G 1.1/2" -11	M 52 x 2	15,0	34,0	55	50	50	55	44.04 x 3.53

结构系列:LL=非常轻 L=轻 S=重 - PN = 额定压力 PB = 最大工作压力 - Ø d2 = 管外直径

## 产品变体

**EWORX** 旋入式螺栓连接,角度90°,带锁紧螺母和切割环的接套