


属性	
接口 1	米制外螺纹,圆柱形
密封形式 1	E型
接口 2	米制外螺纹,圆柱形
密封形式 2	24°内锥
结构类型	回转式螺栓连接,无节流
结构形式	角度90°
标准	DIN 2353 ISO 8434-1
供货范围	接套(不带锁紧螺母和切割环)
原料	钢
表面保护	电镀涂层



提示

有关安装、装入、压力负荷和允许的工作温度的说明请您参阅管螺栓连接的技术信息。

货品

名称	结构系列	工作压力巴	Ø d2 (mm)	G	Ø D (mm)	i (mm)	L1 (mm)	L2 (mm)	L4 (mm)	L7 (mm)	SW (mm)	S1	OR
XSDOM 06 LL	LL	PN 100	6	M 10 x 1	14,5	8,0	23,5	10,5	13,5	19,0	17	17	7.65 x 1.78
XSDOM 08 LL	LL	PN 100	8	M 10 x 1	14,5	8,0	23,5	10,5	13,5	19,0	17	17	7.65 x 1.78
XSDOM NW 04 HL	L	PN 315	6	M 10 x 1	14,0	8,0	24,0	10,5	12,0	19,0	17	17	7.65 x 1.78
XSDOM NW 06 HL	L	PN 315	8	M 12 x 1.5	17,0	12,0	30,0	14,0	14,5	21,5	22	19	11.10 x 1.78
XSDOM NW 08 HL	L	PN 315	10	M 14 x 1.5	19,0	12,0	30,0	14,0	15,5	22,5	22	19	11.10 x 1.78
XSDOM NW 10 HL	L	PN 315	12	M 16 x 1.5	21,0	12,0	36,0	16,5	18,0	25,0	27	24	14.00 x 1.78
XSDOM NW 10 HL 18	L	PN 315	12	M 18 x 1.5	23,5	12,0	35,0	16,5	18,0	25,0	27	24	18.77 x 1.78
XSDOM NW 13 HL	L	PN 315	15	M 18 x 1.5	23,0	12,0	39,5	18,5	21,5	28,5	30	27	18.77 x 1.78
XSDOM NW 16 HL	L	PN 315	18	M 22 x 1.5	27,0	14,0	45,0	21,5	21,0	28,5	32	30	18.77 x 1.78
XSDOM NW 20 HL	L	PN 160	22	M 26 x 1.5	31,0	16,0	53,0	24,0	27,5	35,0	41	36	23.81 x 2.62
XSDOM NW 25 HL	L	PN 160	28	M 33 x 2	39,0	18,0	66,0	30,5	32,0	39,5	50	46	29.82 x 2.62
XSDOM NW 32 HL	L	PN 160	35	M 42 x 2	49,0	20,0	76,0	35,5	36,0	46,5	60	55	37.77 x 2.62
XSDOM NW 40 HL	L	PN 160	42	M 48 x 2	55,0	22,0	87,0	40,5	40,5	51,5	70	60	41.28 x 3.53
XSDOM NW 03 HS	S	PN 400	6	M 12 x 1.5	17,5	12,0	30,0	14,0	16,5	23,5	22	19	11.10 x 1.78
XSDOM NW 04 HS	S	PN 400	8	M 14 x 1.5	19,0	12,0	30,0	14,0	16,5	23,5	22	19	11.10 x 1.78
XSDOM NW 06 HS	S	PN 400	10	M 16 x 1.5	21,0	12,0	35,0	16,5	18,5	26,0	27	24	14.00 x 1.78
XSDOM NW 08 HS	S	PN 400	12	M 18 x 1.5	23,0	12,0	39,5	18,5	20,0	27,5	30	27	18.77 x 1.78
XSDOM NW 10 HS	S	PN 400	14	M 20 x 1.5	25,0	14,0	43,5	20,0	22,5	30,5	32	30	18.77 x 1.78
XSDOM NW 13 HS	S	PN 315	16	M 22 x 1.5	27,0	14,0	45,0	21,5	22,0	30,5	32	30	18.77 x 1.78
XSDOM NW 16 HS	S	PN 315	20	M 27 x 2	32,0	16,0	53,0	24,0	26,5	37,0	41	36	23.81 x 2.62
XSDOM NW 20 HS	S	PN 250	25	M 33 x 2	39,0	18,0	66,0	30,5	31,5	43,5	50	46	29.82 x 2.62
XSDOM NW 25 HS	S	PN 160	30	M 42 x 2	49,0	20,0	76,0	35,5	37,0	50,5	60	55	37.77 x 2.62
XSDOM NW 32 HS	S	PN 160	38	M 48 x 2	55,0	22,0	87,0	40,5	41,5	57,5	70	60	41.28 x 3.53

PN = 额定压力 PB = 最大工作压力 - 结构系列:LL=非常轻 L=轻 S=重 - Ø = 管外直径

产品变体

XSDOM VA	回转式螺栓连接,无节流,角度90°, 不锈钢
SDOM	回转式螺栓连接,无节流,角度90°, 钢