


属性	
接口 1	米制圈眼
接口2	米制外螺纹,圆柱形
密封形式 2	24°内锥
结构类型	连接器,环-螺纹件
结构形式	直道
原料	钢
表面保护	电镀涂层





名称 管外径 Ø (mm) G1 Ø d1 (mm) 用于空心螺钉 (mm) SW (mm) GB 04 HL 6 M 12 x 1.5 10 M 10 17 GB 06 HL 8 M 14 x 1.5 12 M 12 19 GB 08 HL 06 8 M 14 x 1.5 14 M 14 19 GB 08 HL 10 M 16 x 1.5 14 M 14 22 GB 10 HL 12 M 18 x 1.5 16 M 16 24	货品					
GB 06 HL 8 M 14 x 1.5 12 M 12 19 GB 08 HL 06 8 M 14 x 1.5 14 M 14 19 GB 08 HL 10 M 16 x 1.5 14 M 14 22	名称		G1		用于空心螺钉	
GB 08 HL 06 8 M 14 x 1.5 14 M 14 19 GB 08 HL 10 M 16 x 1.5 14 M 14 22	GB 04 HL	6	M 12 x 1.5	10	M 10	17
GB 08 HL 10 M 16 x 1.5 14 M 14 22	GB 06 HL	8	M 14 x 1.5	12	M 12	19
	GB 08 HL 06	8	M 14 x 1.5	14	M 14	19
GB 10 HL 12 M 18 x 1.5 16 M 16 24	GB 08 HL	10	M 16 x 1.5	14	M 14	22
	GB 10 HL	12	M 18 x 1.5	16	M 16	24
GB 13 HL 10 12 M 18 x 1.5 18 M 18 24	GB 13 HL 10	12	M 18 x 1.5	18	M 18	24
GB 13 HL 15 M 22 x 1.5 18 M 18 27	GB 13 HL	15	M 22 x 1.5	18	M 18	27
GB 16 HL 13 15 M 22 x 1.5 22 M 22 27	GB 16 HL 13	15	M 22 x 1.5	22	M 22	27
GB 16 HL 18 M 26 x 1.5 22 M 22 32	GB 16 HL	18	M 26 x 1.5	22	M 22	32

SW = 对应边宽度