

# G HB IN

## 旋上式接套

### 属性

接口 1	BSP外螺纹,圆柱形
密封形式 1	60°内锥
接口 2	NPT内螺纹
密封形式 2	螺纹密封
结构类型	旋上式接套
结构形式	直道
原料	钢
表面保护	电镀涂层



### 货品

名称	G1	G2	SW (mm)
G HB 02 IN	G 1/8" -28	1/8" -27 NPT	14
G HB 02 IN 04	G 1/8" -28	1/4" -18 NPT	19
G HB 04 IN	G 1/4" -19	1/4" -18 NPT	19
G HB 04 IN 06	G 1/4" -19	3/8" -18 NPT	24
G HB 06 IN 04	G 3/8" -19	1/4" -18 NPT	22
G HB 06 IN	G 3/8" -19	3/8" -18 NPT	24
G HB 08 IN	G 1/2" -14	1/2" -14 NPT	27
G HB 12 IN	G 3/4" -14	3/4" -14 NPT	36
G HB 16 IN	G 1" -11	1" -11.5 NPT	41
G HB 20 IN	G 1.1/4" -11	1.1/4" -11.5 NPT	50
G HB 24 IN	G 1.1/2" -11	1.1/2" -11.5 NPT	55

SW = 对应边宽度

### 产品变体

G HB IN VA 旋上式接套, 不锈钢