


GE HRO AJ

旋入式接套

属性

| | |
|--------|------------|
| 接口 1 | BSP外螺纹,圆柱形 |
| 密封形式 1 | G 型 |
| 接口 2 | UN/UNF螺母螺纹 |
| 密封形式 2 | 74°内锥 |
| 结构类型 | 旋入式接套 |
| 结构形式 | 直道 |
| 原料 | 钢 |
| 表面保护 | 电镀涂层 |



货品

| 名称 | G1 | G2 | SW (mm) | S1 | OR |
|-----------------|--------------|----------------|------------|----|--------------|
| GE HRO 02 AJ 04 | G 1/8" -28 | 7/16" -20 UNF | 16 | 16 | 8.00 x 2.00 |
| GE HRO 04 AJ | G 1/4" -19 | 7/16" -20 UNF | 20 | 16 | 10.77 x 2.62 |
| GE HRO 04 AJ 05 | G 1/4" -19 | 1/2" -20 UNF | 20 | 17 | 10.77 x 2.62 |
| GE HRO 04 AJ 08 | G 1/4" -19 | 3/4" -16 UNF | 20 | 22 | 10.77 x 2.62 |
| GE HRO 06 AJ 04 | G 3/8" -19 | 7/16" -20 UNF | 24 | 16 | 13.94 x 2.62 |
| GE HRO 06 AJ 05 | G 3/8" -19 | 1/2" -20 UNF | 24 | 17 | 13.94 x 2.62 |
| GE HRO 06 AJ | G 3/8" -19 | 9/16" -18 UNF | 24 | 19 | 13.94 x 2.62 |
| GE HRO 06 AJ 08 | G 3/8" -19 | 3/4" -16 UNF | 24 | 22 | 13.94 x 2.62 |
| GE HRO 06 AJ 10 | G 3/8" -19 | 7/8" -14 UNF | 24 | 27 | 13.94 x 2.62 |
| GE HRO 08 AJ 06 | G 1/2" -14 | 9/16" -18 UNF | 28 | 19 | 17.86 x 2.62 |
| GE HRO 08 AJ | G 1/2" -14 | 3/4" -16 UNF | 28 | 22 | 17.86 x 2.62 |
| GE HRO 08 AJ 10 | G 1/2" -14 | 7/8" -14 UNF | 28 | 27 | 17.86 x 2.62 |
| GE HRO 08 AJ 12 | G 1/2" -14 | 1.1/16" -12 UN | 28 | 32 | 17.86 x 2.62 |
| GE HRO 12 AJ 10 | G 3/4" -14 | 7/8" -14 UNF | 35 | 27 | 23.47 x 2.62 |
| GE HRO 12 AJ 16 | G 3/4" -14 | 1.5/16" -12 UN | 35 | 38 | 23.47 x 2.62 |
| GE HRO 16 AJ 12 | G 1" -11 | 1.1/16" -12 UN | 43 | 32 | 29.74 x 3.53 |
| GE HRO 16 AJ 20 | G 1" -11 | 1.5/8" -12 UN | 43 | 50 | 29.74 x 3.53 |
| GE HRO 20 AJ 16 | G 1.1/4" -11 | 1.5/16" -12 UN | 52 | 38 | 37.69 x 3.53 |
| GE HRO 20 AJ 24 | G 1.1/4" -11 | 1.7/8" -12 UN | 52 | 58 | 37.69 x 3.53 |

SW, S1, S2 = 对应边宽度