

GE HRO L HJ

旋入式接套,长

HANSA FLEX

属性

| | |
|--------|------------|
| 接口 1 | BSP外螺纹,圆柱形 |
| 密封形式 1 | G 型 |
| 接口 2 | UN/UNF外螺纹 |
| 密封形式 2 | 74°外锥 |
| 结构类型 | 旋入式接套,长 |
| 结构形式 | 直道 |
| 原料 | 钢 |
| 表面保护 | 电镀涂层 |



货品

| 名称 | G1 | G2 | L1 (mm) | L2 (mm) | L3 (mm) | SW (mm) | OR |
|-------------------|--------------|----------------|------------|------------|------------|------------|--------------|
| GE HRO L 02 HJ 04 | G 1/8" -28 | 7/16" -20 UNF | 50,0 | 8 | 35 | 16 | 7.65 x 1.78 |
| GE HRO L 04 HJ | G 1/4" -19 | 7/16" -20 UNF | 55,5 | 12 | 35 | 20 | 10.78 x 2.62 |
| GE HRO L 04 HJ 05 | G 1/4" -19 | 1/2" -20 UNF | 57,5 | 12 | 37 | 20 | 10.78 x 2.62 |
| GE HRO L 04 HJ 06 | G 1/4" -19 | 9/16" -18 UNF | 59,5 | 12 | 39 | 20 | 10.78 x 2.62 |
| GE HRO L 04 HJ 08 | G 1/4" -19 | 3/4" -16 UNF | 68,5 | 12 | 48 | 20 | 10.78 x 2.62 |
| GE HRO L 06 HJ | G 3/8" -19 | 9/16" -18 UNF | 59,5 | 12 | 39 | 24 | 13.94 x 2.62 |
| GE HRO L 06 HJ 05 | G 3/8" -19 | 1/2" -20 UNF | 57,5 | 12 | 37 | 24 | 13.94 x 2.62 |
| GE HRO L 06 HJ 08 | G 3/8" -19 | 3/4" -16 UNF | 68,5 | 12 | 48 | 24 | 13.94 x 2.62 |
| GE HRO L 06 HJ 10 | G 3/8" -19 | 7/8" -14 UNF | 74,0 | 12 | 53 | 24 | 13.94 x 2.62 |
| GE HRO L 08 HJ | G 1/2" -14 | 3/4" -16 UNF | 72,0 | 14 | 48 | 28 | 17.86 x 2.62 |
| GE HRO L 08 HJ 06 | G 1/2" -14 | 9/16" -18 UNF | 63,0 | 14 | 39 | 28 | 17.86 x 2.62 |
| GE HRO L 08 HJ 10 | G 1/2" -14 | 7/8" -14 UNF | 77,0 | 14 | 53 | 28 | 17.86 x 2.62 |
| GE HRO L 08 HJ 12 | G 1/2" -14 | 1.1/16" -12 UN | 88,0 | 14 | 63 | 28 | 17.86 x 2.62 |
| GE HRO L 12 HJ | G 3/4" -14 | 1.1/16" -12 UN | 91,0 | 16 | 63 | 35 | 23.47 x 2.62 |
| GE HRO L 12 HJ 10 | G 3/4" -14 | 7/8" -14 UNF | 81,0 | 16 | 53 | 35 | 23.47 x 2.62 |
| GE HRO L 12 HJ 16 | G 3/4" -14 | 1.5/16" -12 UN | 100,0 | 16 | 72 | 35 | 23.47 x 2.62 |
| GE HRO L 16 HJ | G 1" -11 | 1.5/16" -12 UN | 102,0 | 18 | 72 | 43 | 29.74 x 3.53 |
| GE HRO L 16 HJ 12 | G 1" -11 | 1.1/16" -12 UN | 93,5 | 18 | 63 | 43 | 29.74 x 3.53 |
| GE HRO L 16 HJ 20 | G 1" -11 | 1.5/8" -12 UN | 119,0 | 18 | 88 | 43 | 29.74 x 3.53 |
| GE HRO L 20 HJ | G 1.1/4" -11 | 1.5/8" -12 UN | 119,0 | 18 | 88 | 52 | 37.69 x 3.53 |
| GE HRO L 20 HJ 16 | G 1.1/4" -11 | 1.5/16" -12 UN | 106,0 | 20 | 72 | 52 | 37.69 x 3.53 |
| GE HRO L 20 HJ 24 | G 1.1/4" -11 | 1.7/8" -12 UN | 132,0 | 20 | 98 | 52 | 37.69 x 3.53 |
| GE HRO L 24 HJ | G 1.1/2" -11 | 1.7/8" -12 UN | 136,0 | 22 | 98 | 58 | 44.04 x 3.53 |

SW = 对应边宽度