

属性

应用范围	冷却器软管
标准	DIN 73411
内胶层	EPDM
增强层	ID 08-18:一层聚酯编织, ID≥20, 一层合成纤维编织
外胶层	EPDM(ID≥20, 外胶层表面带花纹)
颜色	黑色
温度 min.	-40 °C
温度 max.	120 °C
适用介质	冷却水 冷却液



货品

名称	ID x 壁	工作压力 (bar)	破裂压力 (bar)	卷长 (m)
KUEHLER 08-3.5	8 x 3.5	4,0	12	40
KUEHLER 10-3.5	10 x 3.5	4,0	12	40
KUEHLER 12-3.5	12 x 3.5	4,0	12	40
KUEHLER 13-3.5	13 x 3.5	4,0	12	40
KUEHLER 15-3.5	15 x 3.5	4,0	12	40
KUEHLER 16-3.5	16 x 3.5	4,0	12	40
KUEHLER 18-3.5	18 x 3.5	4,0	12	40
KUEHLER 20-3.5	20 x 3.5	4,0	12	40
KUEHLER 22-3.5	22 x 3.5	4,0	12	40
KUEHLER 25-3.5	25 x 3.5	4,0	12	40
KUEHLER 28-4	28 x 4	4,0	12	40
KUEHLER 30-4	30 x 4	4,0	12	40
KUEHLER 32-4	32 x 4	4,0	12	40
KUEHLER 35-4	35 x 4	4,0	12	40
KUEHLER 38-5	38 x 5	4,0	12	40
KUEHLER 40-5	40 x 5	4,0	12	40
KUEHLER 42-5	42 x 5	4,0	12	40
KUEHLER 45-5	45 x 5	4,0	12	40
KUEHLER 50-5	50 x 5	4,0	12	40
KUEHLER 55-5	55 x 5	4,0	12	40
KUEHLER 60-5	60 x 5	4,0	12	40
KUEHLER 70-5	70 x 5	4,0	12	40
KUEHLER 90-6	90 x 6	4,0	12	40