

属性

应用范围 介质为水和空气的常规应用

特殊的属性 硬度:约77°肖氏硬度A
环保型,不含重金属
耐磨、耐老化
无毒
持久的透明度
挠性大

内胶层 软PVC

增强层 一层纤维编织增强层


外胶层 软PVC

颜色 透明

温度 min. -5 °C

温度 max. 60 °C

适用介质 水
空气



货品

| 名称 | 内径-Ø (mm) | 外径Ø (mm) | 壁厚 (mm) | BD* 20°C下 (bar) | 最小弯曲半径 (mm) | 卷长 (m) |
|------------|--------------|-------------|------------|--------------------|----------------|-----------|
| PSG 04-3 | 4,0 | 10,0 | 3,0 | 20 | 15 | 50 |
| PSG 05-3 | 5,0 | 11,0 | 3,0 | 20 | 20 | 50 |
| PSG 06-3 | 6,0 | 12,0 | 3,0 | 20 | 25 | 50 |
| PSG 08-3 | 8,0 | 14,0 | 3,0 | 20 | 30 | 50 |
| PSG 09-3 | 9,0 | 15,0 | 3,0 | 15 | 35 | 50 |
| PSG 10-3 | 10,0 | 16,0 | 3,0 | 15 | 40 | 50 |
| PSG 12-3 | 12,0 | 18,0 | 3,0 | 15 | 50 | 50 |
| PSG 12-4.5 | 12,0 | 21,0 | 4,5 | 15 | 50 | 50 |
| PSG 12.5-3 | 12,5 | 18,5 | 3,0 | 15 | 50 | 50 |
| PSG 13-3 | 13,0 | 19,0 | 3,0 | 15 | 60 | 50 |
| PSG 13-3.5 | 13,0 | 20,0 | 3,5 | 15 | 60 | 50 |
| PSG 15-3 | 15,0 | 21,0 | 3,0 | 10 | 75 | 50 |
| PSG 16-3.5 | 16,0 | 23,0 | 3,5 | 10 | 80 | 50 |
| PSG 16-4 | 16,0 | 24,0 | 4,0 | 10 | 80 | 50 |
| PSG 19-3.5 | 19,0 | 26,0 | 3,5 | 10 | 80 | 50 |
| PSG 19-4 | 19,0 | 27,0 | 4,0 | 10 | 100 | 25 / 50 |
| PSG 19-5 | 19,0 | 29,0 | 5,0 | 10 | 100 | 25 / 50 |
| PSG 22-4 | 22,0 | 30,0 | 4,0 | 8 | 180 | 25 / 50 |
| PSG 25-4 | 25,0 | 33,0 | 4,0 | 8 | 200 | 25 / 50 |
| PSG 25-4.5 | 25,0 | 34,0 | 4,5 | 8 | 120 | 25 / 50 |
| PSG 30-4 | 30,0 | 38,0 | 4,0 | 7 | 170 | 25 / 50 |
| PSG 32-5 | 32,0 | 42,0 | 5,0 | 7 | 180 | 25 / 50 |
| PSG 38-5 | 38,0 | 48,0 | 5,0 | 6 | 200 | 25 / 50 |
| PSG 45-5 | 45,0 | 55,0 | 5,0 | 4 | 300 | 25 |
| PSG 50-5 | 50,0 | 60,0 | 5,0 | 4 | 350 | 25 |

BD = 工作压力

产品变体

PSG BLAU 带编织衬里的PVC软管, 蓝色

PSG GRUEN 带编织衬里的PVC软管, 绿色

PSG ROT 带编织衬里的PVC软管, 红色

PSG SCHWARZ 带编织衬里的PVC软管, 黑色