

属性

特殊的属性 硬度:约77°肖氏硬度A

内胶层 软PVC

增强层 没有


外胶层 软PVC

颜色 透明

温度 min. -5 °C

温度 max. 60 °C

适用介质 水
空气



提示

压力值针对的是+20°C下不带压力冲击的短时压力负荷。

货品

| 名称 | 内径Ø (mm) | 外径Ø (mm) | 壁厚 (mm) | BD* 20°C下 (bar) | 卷长 (m) |
|------------|-------------|-------------|------------|--------------------|-----------|
| PSK 02-1 | 2 | 4 | 1,0 | 13,0 | 50 |
| PSK 03-1 | 3 | 5 | 1,0 | 9,5 | 50 |
| PSK 03-1.5 | 3 | 6 | 1,5 | 12,5 | 50 |
| PSK 04-1 | 4 | 6 | 1,0 | 7,5 | 50 |
| PSK 04-1.5 | 4 | 7 | 1,5 | 10,5 | 50 |
| PSK 04-2 | 4 | 8 | 2,0 | 12,5 | 50 |
| PSK 05-1 | 5 | 7 | 1,0 | 6,0 | 50 |
| PSK 05-1.5 | 5 | 8 | 1,5 | 8,5 | 50 |
| PSK 05-2 | 5 | 9 | 2,0 | 10,5 | 50 |
| PSK 05-3.5 | 5 | 12 | 3,5 | 12,5 | 50 |
| PSK 06-1 | 6 | 8 | 1,0 | 5,5 | 50 |
| PSK 06-1.5 | 6 | 9 | 1,5 | 7,5 | 50 |
| PSK 06-2 | 6 | 10 | 2,0 | 9,5 | 50 |
| PSK 06-3 | 6 | 12 | 3,0 | 12,5 | 50 |
| PSK 07-1 | 7 | 9 | 1,0 | 4,5 | 50 |
| PSK 07-1.5 | 7 | 10 | 1,5 | 6,5 | 50 |
| PSK 07-2 | 7 | 11 | 2,0 | 8,5 | 50 |
| PSK 08-1 | 8 | 10 | 1,0 | 4,0 | 50 |
| PSK 08-1.5 | 8 | 11 | 1,5 | 6,0 | 50 |
| PSK 08-2 | 8 | 12 | 2,0 | 7,5 | 50 |
| PSK 08-3 | 8 | 14 | 3,0 | 10,5 | 50 |
| PSK 09-1 | 9 | 11 | 1,0 | 3,5 | 50 |
| PSK 09-1.5 | 9 | 12 | 1,5 | 5,0 | 50 |
| PSK 09-2 | 9 | 13 | 2,0 | 6,5 | 50 |
| PSK 09-2.5 | 9 | 14 | 2,5 | 7,0 | 50 |
| PSK 09-3.5 | 9 | 16 | 3,5 | 10,5 | 50 |
| PSK 10-1.5 | 10 | 13 | 1,5 | 4,5 | 50 |
| PSK 10-2 | 10 | 14 | 2,0 | 6,0 | 50 |
| PSK 10-3 | 10 | 16 | 3,0 | 8,5 | 50 |
| PSK 11-2 | 11 | 15 | 2,0 | 5,5 | 50 |
| PSK 12-1.5 | 12 | 15 | 1,5 | 4,0 | 50 |
| PSK 12-2 | 12 | 16 | 2,0 | 5,0 | 50 |
| PSK 12-2.5 | 12 | 17 | 2,5 | 6,5 | 50 |
| PSK 12-3 | 12 | 18 | 3,0 | 7,5 | 50 |
| PSK 13-2 | 13 | 17 | 2,0 | 5,0 | 50 |
| PSK 13-3 | 13 | 19 | 3,0 | 7,0 | 50 |
| PSK 14-2 | 14 | 18 | 2,0 | 4,5 | 50 |
| PSK 14-2.5 | 14 | 19 | 2,5 | 5,5 | 50 |
| PSK 14-3 | 14 | 20 | 3,0 | 6,0 | 50 |
| PSK 15-2 | 15 | 19 | 2,0 | 7,5 | 50 |
| PSK 15-3 | 15 | 21 | 3,0 | 6,0 | 50 |
| PSK 16-2 | 16 | 20 | 2,0 | 4,0 | 50 |
| PSK 16-2.5 | 16 | 21 | 2,5 | 5,0 | 50 |
| PSK 16-3 | 16 | 22 | 3,0 | 6,0 | 50 |
| PSK 18-2 | 18 | 22 | 2,0 | 3,5 | 50 |
| PSK 18-3 | 18 | 24 | 3,0 | 5,0 | 50 |



货品

| 名称 | 内径Ø (mm) | 外径Ø (mm) | 壁厚 (mm) | BD* 20°C下 (bar) | 卷长 (m) |
|------------|-------------|-------------|------------|--------------------|-----------|
| PSK 19-2.5 | 19 | 24 | 2,5 | 4,5 | 50 |
| PSK 19-3 | 19 | 25 | 3,0 | 5,0 | 50 |
| PSK 19-3.5 | 19 | 26 | 3,5 | 5,5 | 50 |
| PSK 19-4 | 19 | 27 | 4,0 | 6,5 | 50 |
| PSK 20-2 | 20 | 24 | 2,0 | 3,0 | 50 |
| PSK 20-3 | 20 | 26 | 3,0 | 4,5 | 50 |
| PSK 22-3 | 22 | 28 | 3,0 | 4,5 | 50 |
| PSK 22-4 | 22 | 30 | 4,0 | 4,5 | 50 |
| PSK 24-2 | 24 | 28 | 2,0 | 2,5 | 50 |
| PSK 24-3 | 24 | 30 | 3,0 | 4,0 | 50 |
| PSK 25-3 | 25 | 31 | 3,0 | 4,0 | 50 |
| PSK 25-4 | 25 | 33 | 4,0 | 5,0 | 50 |
| PSK 25-4.5 | 25 | 34 | 4,5 | 5,5 | 50 |
| PSK 27-3 | 27 | 33 | 3,0 | 3,5 | 50 |
| PSK 28-4 | 28 | 36 | 4,0 | 4,5 | 50 |
| PSK 30-3.5 | 30 | 37 | 3,5 | 4,0 | 50 |
| PSK 30-4 | 30 | 38 | 4,0 | 4,0 | 50 |
| PSK 30-4.5 | 30 | 39 | 4,5 | 4,5 | 50 |
| PSK 30-5 | 30 | 40 | 5,0 | 5,0 | 50 |
| PSK 32-3.5 | 32 | 39 | 3,5 | 3,0 | 50 |
| PSK 32-4 | 32 | 40 | 4,0 | 4,0 | 50 |
| PSK 32-5 | 32 | 42 | 5,0 | 5,0 | 50 |
| PSK 35-3.5 | 35 | 42 | 3,5 | 3,5 | 50 |
| PSK 35-5 | 35 | 45 | 5,0 | 4,5 | 50 |
| PSK 38-5 | 38 | 48 | 5,0 | 4,0 | 50 |
| PSK 40-4 | 40 | 48 | 4,0 | 3,0 | 50 |
| PSK 40-5 | 40 | 50 | 5,0 | 4,0 | 50 |
| PSK 42-5 | 42 | 52 | 5,0 | 3,5 | 50 |
| PSK 45-5 | 45 | 55 | 5,0 | 3,5 | 25 |
| PSK 50-5 | 50 | 60 | 5,0 | 3,0 | 25 |
| PSK 55-4.5 | 55 | 64 | 4,5 | 2,5 | 25 |
| PSK 60-5 | 60 | 70 | 5,0 | 2,5 | 25 |
| PSK 65-5 | 65 | 75 | 5,0 | 2,5 | 25 |
| PSK 70-5 | 70 | 80 | 5,0 | 2,5 | 25 |
| PSK 75-7.5 | 75 | 90 | 7,5 | 3,4 | 25 |
| PSK 80-5 | 80 | 90 | 5,0 | 2,3 | 25 |
| PSK 90-5 | 90 | 100 | 5,0 | 2,1 | 25 |

BD = 工作压力