

TR WT

PA 12材料制成的塑料管,软

HANSA FLEX

属性

| | |
|---------|--------------------------------|
| 应用范围 | 液压气动控制管路 汽车行业 实验室和食品行业 |
| 特殊的属性 | 耐低温,耐恶劣天气 重量轻 |
| 内胶层 | 聚酰胺 |
| 增强层 | 没有 |
| 外胶层 | 聚酰胺 |
| 颜色 | 透明无色 |
| 温度 min. | -60 °C |
| 温度 max. | 100 °C |
| 温度范围 | 温度峰值至120°C |
| 适用介质 | 矿物油 油脂 燃料 耐受酸,耐碱和盐类溶液 |



提示

从20 °C起请注意压力减小系数。

(最大工作压力 = 工作压力 x 系数)。

温度:20°C / 30°C / 40°C / 50°C / 60°C / 70°C / 80°C / 90°C / 100°C / 110°C / 120°C

因数:1,00 / 0,83 / 0,72 / 0,64 / 0,57 / 0,52 / 0,47 / 0,44 / 0,36 / 0,32 / 0,28

货品

| 名称 | 内径-Ø (mm) | 外径Ø (mm) | 壁厚 (mm) | BD* 20°C下 (bar) | 最小弯曲半径 (mm) |
|-----------------|--------------|-------------|------------|--------------------|----------------|
| TR 04-0.5 WT | 3,0 | 4,0 | 0,500 | 19,0 | 20 |
| TR 04-0.65 WT | 2,7 | 4,0 | 0,650 | 26,0 | 20 |
| TR 04-1 WT | 2,0 | 4,0 | 1,000 | 44,0 | 20 |
| TR 05-0.85 WT | 3,3 | 5,0 | 0,850 | 28,0 | 25 |
| TR 05-1 WT | 3,0 | 5,0 | 1,000 | 34,0 | 25 |
| TR 06-1 WT | 4,0 | 6,0 | 1,000 | 27,0 | 30 |
| TR 06-1.5 WT | 3,0 | 6,0 | 1,500 | 45,0 | 30 |
| TR 08-1 WT | 6,0 | 8,0 | 1,000 | 19,0 | 40 |
| TR 08-1.5 WT | 5,0 | 8,0 | 1,500 | 31,0 | 40 |
| TR 08-2 WT | 4,0 | 8,0 | 2,000 | 45,0 | 40 |
| TR 10-1 WT | 8,0 | 10,0 | 1,000 | 15,0 | 60 |
| TR 10-1.25 WT | 7,5 | 10,0 | 1,250 | 19,0 | 60 |
| TR 10-2 WT | 6,0 | 10,0 | 2,000 | 34,0 | 50 |
| TR 12-1 WT | 10,0 | 12,0 | 1,000 | 12,0 | 55 |
| TR 12-1.5 WT | 9,0 | 12,0 | 1,500 | 19,0 | 60 |
| TR 12-2 WT | 8,0 | 12,0 | 2,000 | 27,0 | 60 |
| TR 12.5-1.25 WT | 10,0 | 12,5 | 1,250 | 15,0 | 75 |
| TR 14-1.5 WT | 11,0 | 14,0 | 1,500 | 16,0 | 80 |
| TR 15-1.5 WT | 12,0 | 15,0 | 1,500 | 15,0 | 90 |
| TR 18-2 WT | 14,0 | 18,0 | 2,000 | 16,0 | 100 |
| TR 20-2 WT | 16,0 | 20,0 | 2,000 | 14,0 | 120 |
| TR 22-2 WT | 18,0 | 22,0 | 2,000 | 13,0 | 150 |
| TR 25-2.5 WT | 20,0 | 25,0 | 2,500 | 14,0 | 150 |
| TR 28-2.5 WT | 23,0 | 28,0 | 2,500 | 13,0 | 150 |
| TR 30-2.5 WT | 25,0 | 30,0 | 2,500 | 8,0 | 260 |

BD = 工作压力

产品变体

| | |
|--------|---------------------|
| TR WB | PA 12材料制成的塑料管,软, 蓝色 |
| TR WGE | PA 12材料制成的塑料管,软, 黄色 |
| TR WR | PA 12材料制成的塑料管,软, 红色 |
| TR WS | PA 12材料制成的塑料管,软, 黑色 |