

SKS HL / SKS HS

插式接合器插头

属性

| | |
|--------|-------------------|
| 应用范围 | 工业、建筑机械和农业技术等一般应用 |
| 接口 1 | 米制外螺纹,圆柱形 |
| 密封形式 1 | 24°内锥 |
| 标准 | 符合ISO 7241-1 A系列 |
| 原料 | 钢 |
| 表面保护 | 电镀涂层 |



提示

标称宽度 10,结构尺寸 3,包括 ED 规格
可选购

描述

插式接合器可实现快速接合。

订购指南

其他压力值和温度值承索提供。

货品

| 名称 | DN* | 结构系列 | 用于管外径-Ø (mm) | 接口螺纹 | 结构尺寸 | 工作压力 (bar) | SF已接合* | 矿物油温度 min. (°C) | 矿物油温度 max. (°C) |
|----------------|-----|------|-----------------|----------|------|---------------|--------|--------------------|--------------------|
| SKS 04 HL 2 | 4 | L | 6 | M 12x1,5 | 2 | 250,0 | 4 | -30 | 100 |
| SKS 06 HL 2 | 6 | L | 8 | M 14x1,5 | 2 | 250,0 | 4 | -30 | 100 |
| SKS 06 HL 3 | 6 | L | 8 | M 14x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 08 HL 2 | 8 | L | 10 | M 16x1,5 | 2 | 250,0 | 4 | -30 | 100 |
| SKS 08 HL 3 | 8 | L | 10 | M 16x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 10 HL 3 | 10 | L | 12 | M 18x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 10 HL 3 ED | 10 | L | 12 | M 18x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 10 HL 4 | 10 | L | 12 | M 18x1,5 | 4 | 225,0 | 4 | -30 | 100 |
| SKS 13 HL 3 | 12 | L | 15 | M 22x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 13 HL 4 | 12 | L | 15 | M 22x1,5 | 4 | 225,0 | 4 | -30 | 100 |
| SKS 16 HL 3 | 16 | L | 18 | M 26x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 16 HL 4 | 16 | L | 18 | M 26x1,5 | 4 | 225,0 | 4 | -30 | 100 |
| SKS 16 HL 5 | 16 | L | 18 | M 26x1,5 | 5 | 225,0 | 4 | -30 | 100 |
| SKS 20 HL 4 | 19 | L | 22 | M 30x2 | 4 | 225,0 | 4 | -30 | 100 |
| SKS 20 HL 5 | 19 | L | 22 | M 30x2 | 5 | 225,0 | 4 | -30 | 100 |
| SKS 25 HL 5 | 25 | L | 28 | M 36x2 | 5 | 225,0 | 4 | -30 | 100 |
| SKS 04 HS 2 | 4 | S | 8 | M 16x1,5 | 2 | 250,0 | 4 | -30 | 100 |
| SKS 06 HS 1 | 6 | S | 10 | M 18x1,5 | 1 | 300,0 | 4 | -25 | 100 |
| SKS 06 HS 2 | 6 | S | 10 | M 18x1,5 | 2 | 250,0 | 4 | -30 | 100 |
| SKS 06 HS 3 | 6 | S | 10 | M 18x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 08 HS 2 | 8 | S | 12 | M 20x1,5 | 2 | 250,0 | 4 | -30 | 100 |
| SKS 08 HS 3 | 8 | S | 12 | M 20x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 10 HS 3 | 10 | S | 14 | M 22x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 10 HS 4 | 10 | S | 14 | M 22x1,5 | 4 | 225,0 | 4 | -30 | 100 |
| SKS 13 HS 3 | 12 | S | 16 | M 24x1,5 | 3 | 225,0 | 4 | -30 | 100 |
| SKS 13 HS 4 | 12 | S | 16 | M 24x1,5 | 4 | 225,0 | 4 | -30 | 100 |
| SKS 16 HS 3 | 16 | S | 20 | M 30x2 | 3 | 225,0 | 4 | -25 | 100 |
| SKS 16 HS 4 | 16 | S | 20 | M 30x2 | 4 | 225,0 | 4 | -30 | 100 |
| SKS 16 HS 5 | 16 | S | 20 | M 30x2 | 5 | 225,0 | 4 | -30 | 100 |
| SKS 20 HS 5 | 19 | S | 25 | M 36x2 | 5 | 225,0 | 4 | -30 | 100 |
| SKS 25 HS 5 | 25 | S | 30 | M 42x2 | 5 | 225,0 | 4 | -30 | 100 |

DN = 额定直径,额定宽度 - SF gek. = 已接合时安全系数

附件

SKS ZUBS 防尘保护,接合器插头,SKS..



