

# SKS HL / SKS HS

## 插式接合器插头

### 属性

应用范围	工业、建筑机械和农业技术等一般应用
接口 1	米制外螺纹,圆柱形
密封形式 1	24°内锥
标准	符合ISO 7241-1 A系列
原料	钢
表面保护	电镀涂层



### 提示

标称宽度 10,结构尺寸 3,包括 ED 规格  
可选购

### 描述

插式接合器可实现快速接合。

### 订购指南

其他压力值和温度值承索提供。

### 货品

名称	DN*	结构系列	用于管外径-Ø (mm)	接口螺纹	结构尺寸	工作压力 (bar)	SF已接合*	矿物油温度 min. (°C)	矿物油温度 max. (°C)
SKS 04 HL 2	4	L	6	M 12x1,5	2	250,0	4	-30	100
SKS 06 HL 2	6	L	8	M 14x1,5	2	250,0	4	-30	100
SKS 06 HL 3	6	L	8	M 14x1,5	3	225,0	4	-30	100
SKS 08 HL 2	8	L	10	M 16x1,5	2	250,0	4	-30	100
SKS 08 HL 3	8	L	10	M 16x1,5	3	225,0	4	-30	100
SKS 10 HL 3	10	L	12	M 18x1,5	3	225,0	4	-30	100
SKS 10 HL 3 ED	10	L	12	M 18x1,5	3	225,0	4	-30	100
SKS 10 HL 4	10	L	12	M 18x1,5	4	225,0	4	-30	100
SKS 13 HL 3	12	L	15	M 22x1,5	3	225,0	4	-30	100
SKS 13 HL 4	12	L	15	M 22x1,5	4	225,0	4	-30	100
SKS 16 HL 3	16	L	18	M 26x1,5	3	225,0	4	-30	100
SKS 16 HL 4	16	L	18	M 26x1,5	4	225,0	4	-30	100
SKS 16 HL 5	16	L	18	M 26x1,5	5	225,0	4	-30	100
SKS 20 HL 4	19	L	22	M 30x2	4	225,0	4	-30	100
SKS 20 HL 5	19	L	22	M 30x2	5	225,0	4	-30	100
SKS 25 HL 5	25	L	28	M 36x2	5	225,0	4	-30	100
SKS 04 HS 2	4	S	8	M 16x1,5	2	250,0	4	-30	100
SKS 06 HS 1	6	S	10	M 18x1,5	1	300,0	4	-25	100
SKS 06 HS 2	6	S	10	M 18x1,5	2	250,0	4	-30	100
SKS 06 HS 3	6	S	10	M 18x1,5	3	225,0	4	-30	100
SKS 08 HS 2	8	S	12	M 20x1,5	2	250,0	4	-30	100
SKS 08 HS 3	8	S	12	M 20x1,5	3	225,0	4	-30	100
SKS 10 HS 3	10	S	14	M 22x1,5	3	225,0	4	-30	100
SKS 10 HS 4	10	S	14	M 22x1,5	4	225,0	4	-30	100
SKS 13 HS 3	12	S	16	M 24x1,5	3	225,0	4	-30	100
SKS 13 HS 4	12	S	16	M 24x1,5	4	225,0	4	-30	100
SKS 16 HS 3	16	S	20	M 30x2	3	225,0	4	-25	100
SKS 16 HS 4	16	S	20	M 30x2	4	225,0	4	-30	100
SKS 16 HS 5	16	S	20	M 30x2	5	225,0	4	-30	100
SKS 20 HS 5	19	S	25	M 36x2	5	225,0	4	-30	100
SKS 25 HS 5	25	S	30	M 42x2	5	225,0	4	-30	100

DN = 额定直径,额定宽度 - SF gek. = 已接合时安全系数

### 附件

SKS ZUBS 防尘保护,接合器插头,SKS..



