

属性	
应用范围	工业、建筑机械和农业技术等一般应用
接口 1	NPT内螺纹
密封形式 1	螺纹密封式
与兼容	Pioneer
附加特性	带球阀
原料	钢
表面保护	电镀涂层



描述

插式接合器可实现快速接合。

订购指南

其他压力值和温度值承索提供。

货品

DN*	接口螺纹	L	工作压力	SF已接合*	矿物油温度 min.	矿物油温度 max.
		(mm)	(bar)		(°C)	(°C)
6	NPT 1/4" -18	35,3	200,0	4	-25	110
10	NPT 3/8" -18	38,0	200,0	4	-25	110
12	NPT 1/2" -14	51,4	200,0	4	-25	125
12	NPT 3/4" -14	54,4	200,0	-	-40	110
19	NPT 3/4" -14	46,0	200,0	4	-25	110
25	NPT 1" -11,5	64,3	200,0	4	-25	110
	6 10 12 12 19	6 NPT 1/4" -18 10 NPT 3/8" -18 12 NPT 1/2" -14 12 NPT 3/4" -14 19 NPT 3/4" -14	6 NPT 1/4" -18 35,3 10 NPT 3/8" -18 38,0 12 NPT 1/2" -14 51,4 12 NPT 3/4" -14 54,4 19 NPT 3/4" -14 46,0	(mm) (bar) 6 NPT 1/4" -18 35,3 200,0 10 NPT 3/8" -18 38,0 200,0 12 NPT 1/2" -14 51,4 200,0 12 NPT 3/4" -14 54,4 200,0 19 NPT 3/4" -14 46,0 200,0	(mm) (bar) 6 NPT 1/4" -18 35,3 200,0 4 10 NPT 3/8" -18 38,0 200,0 4 12 NPT 1/2" -14 51,4 200,0 4 12 NPT 3/4" -14 54,4 200,0 - 19 NPT 3/4" -14 46,0 200,0 4	(mm) (bar) (°C) 6 NPT 1/4" -18 35,3 200,0 4 -25 10 NPT 3/8" -18 38,0 200,0 4 -25 12 NPT 1/2" -14 51,4 200,0 4 -25 12 NPT 3/4" -14 54,4 200,0 - -40 19 NPT 3/4" -14 46,0 200,0 4 -25

DN = 额定直径,额定宽度 - SF gek. = 已接合时安全系数

附件

SKS ZUBS SP 防尘保护,接合器插头,SKS..SP