


属性	
接口 1	米制螺母螺纹
密封形式 1	24°/60° Universal sealing head
缩略词	DKL
原料	钢
表面保护	电镀涂层





提示

未损坏的内接头可再次使用。

货品								
名称	DN	尺寸	英寸	G1	用于管外径-Ø (mm)	L1 (mm)	L2 (mm)	S1
ND 06 AFL 04 45	6	4	1/4"	M 12 x 1.5	6	51,0	16,0	14
ND 06 AFL 45	6	4	1/4"	M 14 x 1.5	8	51,0	16,0	17
ND 10 AFL 08 45	10	6	3/8"	M 16 x 1.5	10	58,0	18,0	19
ND 10 AFL 45	10	6	3/8"	M 18 x 1.5	12	59,0	18,0	22
ND 13 AFL 45	12	8	1/2"	M 22 x 1.5	15	68,0	19,0	27
ND 16 AFL 45	16	10	5/8"	M 26 x 1.5	18	81,0	21,0	32
ND 20 AFL 45	19	12	3/4"	M 30 x 2	22	88,0	23,0	36
ND 25 AFL 45	25	16	1"	M 36 x 2	28	105,0	30,0	41

附件

ND ASR GE, RO, BL 插式内接头用止挡圈