


ND HB

插式内接头,AGR

属性

| | |
|--------|-----------------------|
| 接口 1 | BSP外螺纹,圆柱形 |
| 密封形式 1 | 60°内锥 |
| 缩略词 | AGR |
| 标准 | ISO 8434-6 BS 5200 |
| 原料 | 钢 |
| 表面保护 | 电镀涂层 |



提示

未损坏的内接头可再次使用。

货品

| 名称 | DN | 尺寸 | 英寸 | G1 | L1 (mm) | S1 |
|-------------|----|----|------|------------|------------|----|
| ND 06 HB 02 | 6 | 4 | 1/4" | G 1/8" -28 | 36,0 | 17 |
| ND 06 HB | 6 | 4 | 1/4" | G 1/4" -19 | 41,0 | 19 |
| ND 10 HB 06 | 10 | 6 | 3/8" | G 1/4" -19 | 44,0 | 19 |
| ND 10 HB | 10 | 6 | 3/8" | G 3/8" -19 | 45,0 | 22 |
| ND 13 HB | 12 | 8 | 1/2" | G 1/2" -14 | 53,0 | 27 |
| ND 16 HB 13 | 16 | 10 | 5/8" | G 1/2" -14 | - | - |
| ND 16 HB | 16 | 10 | 5/8" | G 5/8" -14 | 65,0 | 30 |
| ND 20 HB | 19 | 12 | 3/4" | G 3/4" -14 | 65,0 | 32 |

附件

ND ASR GE, RO, BL 插式内接头用止挡圈