


PA 500 SF9 45 A

压力连接附件, SFS-CAT W45°

属性

| | |
|--------|-------------------|
| 应用范围 | HD 500软管用压力连接附件 |
| 接口 1 | SAE法兰接口 6000 PSI |
| 密封形式 1 | 用SF-O形圈扁平密封 |
| 缩略词 | SFS-CAT |
| 适用于 | Caterpillar |
| 接入 | 带拉断保护 (Interlock) |
| 供货范围 | 压力内接头 + 压力卡套 |
| 原料 | 钢 |
| 表面保护 | 电镀涂层 |



货品

| 名称 | DN | 尺寸 | 英寸 | 法兰大小 | D (mm) | H (mm) | L1 (mm) | L2 (mm) |
|--------------------|----|----|--------|--------|-----------|-----------|------------|------------|
| PA 720 SF9 45 | 19 | 12 | 3/4" | 3/4" | 41,3 | 14,2 | 139,0 | 34,0 |
| PA 720 SF9 25 45 | 19 | 12 | 3/4" | 1" | 47,6 | 14,2 | 143,0 | 37,5 |
| PA 725 SF9 20 45 | 25 | 16 | 1" | 3/4" | 41,3 | 14,2 | 157,0 | 35,0 |
| PA 725 SF9 45 | 25 | 16 | 1" | 1" | 47,6 | 14,2 | 167,0 | 36,5 |
| PA 725 SF9 32 45 | 25 | 16 | 1" | 1.1/4" | 54,0 | 14,2 | 172,0 | 41,5 |
| PA 532 SF9 25 45 A | 31 | 20 | 1.1/4" | 1" | 47,6 | 14,0 | 174,0 | 39,5 |
| PA 532 SF9 45 A | 31 | 20 | 1.1/4" | 1.1/4" | 54,0 | 14,0 | 194,0 | 44,5 |
| PA 532 SF9 40 45 A | 31 | 20 | 1.1/4" | 1.1/2" | 63,5 | 14,0 | 198,0 | 48,5 |
| PA 540 SF9 32 45 A | 38 | 24 | 1.1/2" | 1.1/4" | 54,0 | 14,0 | 205,5 | 47,0 |
| PA 540 SF9 45 A | 38 | 24 | 1.1/2" | 1.1/2" | 63,5 | 14,0 | 226,0 | 51,0 |