


| 属性     |                        |  |  |  |  |  |  |  |
|--------|------------------------|--|--|--|--|--|--|--|
| 接口1    | SAE法兰接口 3000 PSI       |  |  |  |  |  |  |  |
| 密封形式 1 | 用SF-O形圈扁平密封            |  |  |  |  |  |  |  |
| 缩略词    | SFL                    |  |  |  |  |  |  |  |
| 标准     | SAE J518<br>ISO 6162-1 |  |  |  |  |  |  |  |
| 供货范围   | 压力内接头 + 压力卡套           |  |  |  |  |  |  |  |
| 原料     | 钢                      |  |  |  |  |  |  |  |
| 表面保护   | 电镀涂层                   |  |  |  |  |  |  |  |





| 货品               |    |    |        |        |      |      |       |      |  |
|------------------|----|----|--------|--------|------|------|-------|------|--|
| 名称               | DN | 尺寸 | 英寸     | 法兰大小   | D    | Н    | L1    | L2   |  |
|                  |    |    |        |        | (mm) | (mm) | (mm)  | (mm) |  |
| PAY 316 SF 20 90 | 16 | 10 | 5/8"   | 3/4"   | 38,1 | 6,7  | 98,5  | 54,0 |  |
| PAY 325 SF 90    | 25 | 16 | 1"     | 1"     | 44,4 | 8,0  | 116,0 | 69,0 |  |
| PAY 332 SF 90    | 31 | 20 | 1.1/4" | 1.1/4" | 50,8 | 8,0  | 165,0 | 82,0 |  |