


属性

应用范围	用于HD 100至HD 400、KP、TE软管的压力内接头
接口 1	米制螺母螺纹
密封形式 1	24°/60° Universal sealing head
缩略词	DKL
结构系列	轻
原料	钢
表面保护	电镀涂层



提示

请根据软管类型选择合适的卡套。

货品

名称	DN	尺寸	英寸	工作压力 (bar)	G1	用于管外径-Ø (mm)	L1 (mm)	S1
PN 04 AFL	5	3	3/16"	250,0	M 12 x 1.5	6	41,2	14
PN 06 AFL 04	6	4	1/4"	250,0	M 12 x 1.5	6	45,0	14
PN 06 AFL	6	4	1/4"	250,0	M 14 x 1.5	8	47,0	17
PN 06 AFL 08	6	4	1/4"	250,0	M 16 x 1.5	10	47,5	19
PN 06 AFL 10	6	4	1/4"	250,0	M 18 x 1.5	12	48,5	22
PN 08 AFL	8	5	5/16"	250,0	M 16 x 1.5	10	47,5	19
PN 08 AFL 10	8	5	5/16"	250,0	M 18 x 1.5	12	48,5	22
PN 10 AFL 06	10	6	3/8"	250,0	M 14 x 1.5	8	49,5	17
PN 10 AFL 08	10	6	3/8"	250,0	M 16 x 1.5	10	49,0	19
PN 10 AFL	10	6	3/8"	250,0	M 18 x 1.5	12	50,0	22
PN 10 AFL 13	10	6	3/8"	250,0	M 22 x 1.5	15	50,5	27
PN 13 AFL	12	8	1/2"	250,0	M 22 x 1.5	15	51,5	27
PN 13 AFL 16	12	8	1/2"	160,0	M 26 x 1.5	18	54,0	32
PN 16 AFL 13	16	10	5/8"	160,0	M 22 x 1.5	15	56,0	27
PN 16 AFL	16	10	5/8"	160,0	M 26 x 1.5	18	58,5	32
PN 20 AFL	19	12	3/4"	160,0	M 30 x 2	22	66,0	36
PN 20 AFL 25	19	12	3/4"	100,0	M 36 x 2	28	67,0	41
PN 25 AFL	25	16	1"	100,0	M 36 x 2	28	75,0	41
PN 32 AFL	31	20	1.1/4"	100,0	M 45 x 2	35	88,0	50
PN 40 AFL	38	24	1.1/2"	100,0	M 52 x 2	42	92,5	60

产品变体

PN AFL VA 压力内接头,DKL, 不锈钢