


PN FS 45

压力内接头, BES W45°

属性

应用范围	用于HD 100至HD 400、KP、TE软管的压力内接头
接口 1	管接头
密封形式 1	切割环接口
缩略词	BES
标准	ISO 8434-1
结构系列	重
原料	钢
表面保护	电镀涂层



提示

切割环最终安装必须在硬化的预安装接套(VOM...)中进行。
 请根据软管类型选择合适的卡套。
 不能应用在新结构中;我们推荐:PN...AOS...45。

货品

名称	DN	尺寸	英寸	工作压力 (bar)	D2 (mm)	L1 (mm)	L2 (mm)
PN 04 FS 45	5	3	3/16"	630,0	8,0	59,0	20,0
PN 06 FS 45	6	4	1/4"	630,0	10,0	80,0	23,5
PN 06 FS 08 45	6	4	1/4"	630,0	12,0	82,5	22,0
PN 08 FS 45	8	5	5/16"	630,0	12,0	90,0	25,0
PN 10 FS 45	10	6	3/8"	630,0	14,0	82,5	27,0
PN 13 FS 10 45	12	8	1/2"	400,0	14,0	82,5	27,0
PN 13 FS 45	12	8	1/2"	400,0	16,0	97,0	30,0
PN 16 FS 13 45	16	10	5/8"	400,0	16,0	101,5	30,0
PN 16 FS 45	16	10	5/8"	400,0	20,0	106,0	34,0
PN 20 FS 16 45	19	12	3/4"	400,0	20,0	113,0	34,0
PN 20 FS 45	19	12	3/4"	400,0	25,0	126,0	39,0
PN 25 FS 20 45	25	16	3/4"	250,0	25,0	135,0	39,0
PN 25 FS 45	25	16	1"	250,0	30,0	146,0	44,0
PN 32 FS 25 45	31	20	1.1/4"	250,0	30,0	153,5	44,0
PN 32 FS 45	31	20	1.1/4"	250,0	38,0	172,5	51,0
PN 40 FS 32 45	38	24	1.1/2"	250,0	38,0	176,5	51,0

产品变体

PN FS 45 VA 压力内接头, BES W45°, 不锈钢