


属性	
接口 1	米制外螺纹,圆柱形
密封形式 1	60°内锥
缩略词	AGM
原料	钢
表面保护	电镀涂层





提示

请根据软管类型选择合适的卡套。

货品						
DN	尺寸	英寸	Ø D (mm)	G1		
3	2	1/8"	5,0	M 10 x 1		
4	3	3/16"	6,0	M 12 x 1.5		
6	4	1/4"	8,0	M 14 x 1.5		
8	5	5/16"	10,0	M 16 x 1.5		
10	6	3/8"	12,0	M 18 x 1.5		
12	8	1/2"	15,0	M 22 x 1.5		
12	8	1/2"	15,0	M 26 x 1.5		
16	10	5/8"	18,0	M 26 x 1.5		
	3 4 6 8 10 12	3 2 4 3 6 4 8 5 10 6 12 8 12 8	3 2 1/8" 4 3 3/16" 6 4 1/4" 8 5 5/16" 10 6 3/8" 12 8 1/2" 12 8 1/2"	(mm) 3 2 1/8" 5,0 4 3 3/16" 6,0 6 4 1/4" 8,0 8 5 5/16" 10,0 10 6 3/8" 12,0 12 8 1/2" 15,0 12 8 1/2" 15,0		