


| 属性 | | | | | |
|--------|------------------------------------|--|--|--|--|
| 接口 1 | BSP外螺纹,圆柱形 | | | | |
| 密封形式 1 | 60°内锥 | | | | |
| 缩略词 | AGR | | | | |
| 标准 | ISO 228-1 ISO 8434-6 BS 5200 | | | | |
| 原料 | 黄铜 | | | | |





提示

请根据软管类型选择合适的卡套。

| 货品 | | | | | | |
|--------------|----|----|-------|-------------|------------|--|
| 名称 | DN | 尺寸 | 英寸 | Ø D (mm) | G1 | |
| SIN 03 HB 04 | 3 | 2 | 1/8" | 5,0 | G 1/8" -28 | |
| SIN 04 HB 06 | 4 | 3 | 3/16" | 6,0 | G 1/4" -19 | |
| SIN 06 HB | 6 | 4 | 1/4" | 8,0 | G 1/4" -19 | |
| SIN 06 HB 10 | 6 | 4 | 1/4" | 8,0 | G 3/8" -19 | |
| SIN 08 HB 10 | 8 | 5 | 5/16" | 10,0 | G 3/8" -19 | |
| SIN 10 HB 13 | 10 | 6 | 3/8" | 12,0 | G 1/2" -14 | |
| SIN 13 HB | 12 | 8 | 1/2" | 15,0 | G 1/2" -14 | |