

属性

应用 用于金属切削加工的冷却剂和润滑剂管道。

规格 带PVC内软管的钢承载螺旋线圈
两面钢制旋入式管接头
表面镀镍

属性 绝对密封
可用手弯曲到几乎任何位置
耐用
耐油、脂等



订购指南

其它尺寸承索

货品

| 名称 | G1 | G2 | ID (mm) | S1 (mm) | 额定长度 (+/-5 mm) |
|--------------|--------|--------|------------|------------|----------------|
| UPG G1/8-250 | R 1/8" | R 1/8" | 8,0 | 15,0 | 250 |
| UPG G1/8-320 | R 1/8" | R 1/8" | 8,0 | 15,0 | 320 |
| UPG G1/8-400 | R 1/8" | R 1/8" | 8,0 | 15,0 | 400 |
| UPG G1/8-500 | R 1/8" | R 1/8" | 8,0 | 15,0 | 500 |
| UPG G1/4-200 | R 1/4" | R 1/4" | 10,0 | 19,0 | 200 |
| UPG G1/4-250 | R 1/4" | R 1/4" | 10,0 | 19,0 | 250 |
| UPG G1/4-320 | R 1/4" | R 1/4" | 10,0 | 19,0 | 320 |
| UPG G1/4-400 | R 1/4" | R 1/4" | 10,0 | 19,0 | 400 |
| UPG G1/4-500 | R 1/4" | R 1/4" | 10,0 | 19,0 | 500 |
| UPG G1/4-630 | R 1/4" | R 1/4" | 10,0 | 19,0 | 630 |
| UPG G1/4-800 | R 1/4" | R 1/4" | 10,0 | 19,0 | 800 |
| UPG G3/8-200 | R 3/8" | R 3/8" | 10,0 | 24,0 | 200 |
| UPG G3/8-320 | R 3/8" | R 3/8" | 10,0 | 24,0 | 320 |
| UPG G3/8-400 | R 3/8" | R 3/8" | 10,0 | 24,0 | 400 |
| UPG G3/8-500 | R 3/8" | R 3/8" | 10,0 | 24,0 | 500 |
| UPG G3/8-630 | R 3/8" | R 3/8" | 10,0 | 24,0 | 630 |
| UPG G3/8-800 | R 3/8" | R 3/8" | 10,0 | 24,0 | 800 |
| UPG G1/2-500 | R 1/2" | R 1/2" | 10,0 | 27,0 | 500 |
| UPG G1/2-630 | R 1/2" | R 1/2" | 10,0 | 27,0 | 630 |
| UPG G1/2-800 | R 1/2" | R 1/2" | 10,0 | 27,0 | 800 |