


T HRO HB

旋入式接套,T形

属性

| | |
|------------|-------------|
| 接口 1 | BSP外螺纹,圆柱形 |
| 密封形式 1 | G 型 |
| 接口 2 + 3 | BSP外螺纹,圆柱形 |
| 密封形式 2 + 3 | 60°内锥 |
| 结构类型 | 方向可调节的旋入式接套 |
| 结构形式 | T形 |
| 原料 | 钢 |
| 表面保护 | 电镀涂层 |



货品

| 名称 | G1 | G2 - G3 | SW (mm) | S1 | OR |
|----------------|--------------|--------------|------------|----|--------------|
| T HRO 02 HB | G 1/8" -28 | G 1/8" -28 | 11 | 16 | 7.65 x 1.78 |
| T HRO 04 HB 02 | G 1/4" -19 | G 1/8" -28 | 14 | 20 | 10.78 x 2.62 |
| T HRO 04 HB | G 1/4" -19 | G 1/4" -19 | 19 | 20 | 10.78 x 2.62 |
| T HRO 04 HB 06 | G 1/4" -19 | G 3/8" -19 | 14 | 20 | 10.78 x 2.62 |
| T HRO 06 HB 04 | G 3/8" -19 | G 1/4" -19 | 19 | 24 | 13.94 x 2.62 |
| T HRO 06 HB | G 3/8" -19 | G 3/8" -19 | 19 | 24 | 13.94 x 2.62 |
| T HRO 06 HB 08 | G 3/8" -19 | G 1/2" -14 | 19 | 24 | 13.94 x 2.62 |
| T HRO 08 HB 06 | G 1/2" -14 | G 3/8" -19 | 22 | 28 | 17.86 x 2.62 |
| T HRO 08 HB | G 1/2" -14 | G 1/2" -14 | 22 | 28 | 17.86 x 2.62 |
| T HRO 08 HB 10 | G 1/2" -14 | G 5/8" -14 | 22 | 28 | 17.86 x 2.62 |
| T HRO 08 HB 12 | G 1/2" -14 | G 3/4" -14 | 27 | 28 | 17.86 x 2.62 |
| T HRO 12 HB 08 | G 3/4" -14 | G 1/2" -14 | 27 | 35 | 23.47 x 2.62 |
| T HRO 12 HB | G 3/4" -14 | G 3/4" -14 | 27 | 35 | 23.47 x 2.62 |
| T HRO 12 HB 16 | G 3/4" -14 | G 1" -11 | 33 | 35 | 23.47 x 2.62 |
| T HRO 16 HB 12 | G 1" -11 | G 3/4" -14 | 33 | 43 | 29.74 x 3.53 |
| T HRO 16 HB | G 1" -11 | G 1" -11 | 33 | 43 | 29.74 x 3.53 |
| T HRO 20 HB 16 | G 1.1/4" -11 | G 1" -11 | 41 | 52 | 37.69 x 3.53 |
| T HRO 20 HB | G 1.1/4" -11 | G 1.1/4" -11 | 41 | 52 | 37.69 x 3.53 |
| T HRO 24 HB | G 1.1/2" -11 | G 1.1/2" -11 | 50 | 58 | 44.04 x 3.53 |

SW, S1, S2 = 对应边宽度