

# GMM 100 HFR

注有甘油的压力表

**HANSA FLEX**

## 属性

|        |   |
|--------|---|
| 结构类型   | Pipe spring pressure gauge with glycerine filling |
| 固定     | 带固定钻孔的前环  |
| 接口 1   | BSP外螺纹,圆柱形  |
| 密封形式 1 | 带塞扁平密封  |
| 接口     | 后,偏心  |
| 标准     | EN 837-1  |
| 缓冲     | 通过甘油注入  |
| 温度范围   | medium max. +60 °C<br>Ambient -20 °C to +60 °C    |



## 提示

静止负荷时应用范围: 3/4 x 刻度盘终端读数。

交变负荷时应用范围: 2/3 x 刻度盘终端读数。

## 货品

| 名称               | 额定大小 Ø | 刻度范围     | 质量等级 | 接口         |
|------------------|--------|----------|------|------------|
| GMM 100-0.6 HFR  | 100    | 0...0,6  | 1,0  | G 1/2" -14 |
| GMM 100-1 HFR    | 100    | 0...1    | 1,0  | G 1/2" -14 |
| GMM 100-1.6 HFR  | 100    | 0...1,6  | 1,0  | G 1/2" -14 |
| GMM 100-2.5 HFR  | 100    | 0...2,5  | 1,0  | G 1/2" -14 |
| GMM 100-4 HFR    | 100    | 0...4    | 1,0  | G 1/2" -14 |
| GMM 100-6 HFR    | 100    | 0...6    | 1,0  | G 1/2" -14 |
| GMM 100-10 HFR   | 100    | 0...10   | 1,0  | G 1/2" -14 |
| GMM 100-16 HFR   | 100    | 0...16   | 1,0  | G 1/2" -14 |
| GMM 100-25 HFR   | 100    | 0...25   | 1,0  | G 1/2" -14 |
| GMM 100-40 HFR   | 100    | 0...40   | 1,0  | G 1/2" -14 |
| GMM 100-60 HFR   | 100    | 0...60   | 1,0  | G 1/2" -14 |
| GMM 100-100 HFR  | 100    | 0...100  | 1,0  | G 1/2" -14 |
| GMM 100-160 HFR  | 100    | 0...160  | 1,0  | G 1/2" -14 |
| GMM 100-250 HFR  | 100    | 0...250  | 1,0  | G 1/2" -14 |
| GMM 100-400 HFR  | 100    | 0...400  | 1,0  | G 1/2" -14 |
| GMM 100-600 HFR  | 100    | 0...600  | 1,0  | G 1/2" -14 |
| GMM 100-1000 HFR | 100    | 0...1000 | 1,0  | G 1/2" -14 |