

GMM 160 H

注有甘油的压力表

属性

结构类型	Pipe spring pressure gauge with glycerine filling
接口 1	BSP外螺纹,圆柱形
密封形式 1	带塞扁平密封
接口	后,偏心
标准	EN 837-1
缓冲	通过甘油注入
温度范围	medium max. +60 °C Ambient -20 °C to +60 °C



提示

静止负荷时应用范围: 3/4 x 刻度盘终端读数。

交变负荷时应用范围: 2/3 x 刻度盘终端读数。

货品

名称	额定大小 Ø	刻度范围	质量等级	接口
GMM 160-1 H	160	0...1	1,0	G 1/2" -14
GMM 160-1.6 H	160	0...1,6	1,0	G 1/2" -14
GMM 160-2.5 H	160	0...2,5	1,0	G 1/2" -14
GMM 160-4 H	160	0...4	1,0	G 1/2" -14
GMM 160-6 H	160	0...6	1,0	G 1/2" -14
GMM 160-10 H	160	0...10	1,0	G 1/2" -14
GMM 160-16 H	160	0...16	1,0	G 1/2" -14
GMM 160-25 H	160	0...25	1,0	G 1/2" -14
GMM 160-40 H	160	0...40	1,0	G 1/2" -14
GMM 160-60 H	160	0...60	1,0	G 1/2" -14
GMM 160-100 H	160	0...100	1,0	G 1/2" -14
GMM 160-160 H	160	0...160	1,0	G 1/2" -14
GMM 160-250 H	160	0...250	1,0	G 1/2" -14
GMM 160-400 H	160	0...400	1,0	G 1/2" -14
GMM 160-600 H	160	0...600	1,0	G 1/2" -14
GMM 160-1000 H	160	0...1000	1,0	G 1/2" -14