

属性

| | |
|--------|--|
| 结构类型 | Pipe spring pressure gauge without glycerine filling |
| 接口 1 | BSP外螺纹,圆柱形 |
| 密封形式 1 | 带塞扁平密封 |
| 接口 | 下 |
| 标准 | EN 837-1 |
| 温度范围 | medium max. +60 °C Ambient -20 °C to +60 °C |



提示

静止负荷时应用范围: 3/4 x 刻度盘终端读数。

交变负荷时应用范围: 2/3 x 刻度盘终端读数。

货品

| 名称 | 额定大小 Ø | 刻度范围 | 质量等级 | 接口 |
|----------------|--------|---------|------|------------|
| RMM 40-1-1/8 | 40 | 0...1 | 2,5 | G 1/8" -28 |
| RMM 40-1.6-1/8 | 40 | 0...1,6 | 2,5 | G 1/8" -28 |
| RMM 40-2.5-1/8 | 40 | 0...2,5 | 2,5 | G 1/8" -28 |
| RMM 40-4-1/8 | 40 | 0...4 | 2,5 | G 1/8" -28 |
| RMM 40-6-1/8 | 40 | 0...6 | 2,5 | G 1/8" -28 |
| RMM 40-10-1/8 | 40 | 0...10 | 2,5 | G 1/8" -28 |
| RMM 40-16-1/8 | 40 | 0...16 | 2,5 | G 1/8" -28 |
| RMM 40-25-1/8 | 40 | 0...25 | 2,5 | G 1/8" -28 |
| RMM 40-40-1/8 | 40 | 0...40 | 2,5 | G 1/8" -28 |
| RMM 40-60-1/8 | 40 | 0...60 | 2,5 | G 1/8" -28 |
| RMM 40-100-1/8 | 40 | 0...100 | 2,5 | G 1/8" -28 |
| RMM 40-160-1/8 | 40 | 0...160 | 2,5 | G 1/8" -28 |
| RMM 40-250-1/8 | 40 | 0...250 | 2,5 | G 1/8" -28 |
| RMM 40-315-1/8 | 40 | 0...315 | 2,5 | G 1/8" -28 |
| RMM 40-400-1/8 | 40 | 0...400 | 2,5 | G 1/8" -28 |
| RMM 40-1 | 40 | 0...1 | 2,5 | G 1/4" -19 |
| RMM 40-1.6 | 40 | 0...1,6 | 2,5 | G 1/4" -19 |
| RMM 40-2.5 | 40 | 0...2,5 | 2,5 | G 1/4" -19 |
| RMM 40-4 | 40 | 0...4 | 2,5 | G 1/4" -19 |
| RMM 40-6 | 40 | 0...6 | 2,5 | G 1/4" -19 |
| RMM 40-10 | 40 | 0...10 | 2,5 | G 1/4" -19 |
| RMM 40-16 | 40 | 0...16 | 2,5 | G 1/4" -19 |
| RMM 40-25 | 40 | 0...25 | 2,5 | G 1/4" -19 |
| RMM 40-40 | 40 | 0...40 | 2,5 | G 1/4" -19 |
| RMM 40-60 | 40 | 0...60 | 2,5 | G 1/4" -19 |
| RMM 40-100 | 40 | 0...100 | 2,5 | G 1/4" -19 |
| RMM 40-160 | 40 | 0...160 | 2,5 | G 1/4" -19 |
| RMM 40-250 | 40 | 0...250 | 2,5 | G 1/4" -19 |
| RMM 40-315 | 40 | 0...315 | 2,5 | G 1/4" -19 |
| RMM 40-400 | 40 | 0...400 | 2,5 | G 1/4" -19 |