

# RMM 40 H

## 未注入甘油的压力表

### 属性

结构类型	Pipe spring pressure gauge without glycerine filling
接口 1	BSP外螺纹,圆柱形
密封形式 1	带塞扁平密封
接口	后,中心
标准	EN 837-1
温度范围	medium max. +60 °C Ambient -20 °C to +60 °C



### 提示

静止负荷时应用范围: 3/4 x 刻度盘终端读数。

交变负荷时应用范围: 2/3 x 刻度盘终端读数。

### 货品

名称	额定大小 Ø	刻度范围	质量等级	接口
RMM 40-1-1/8 H	40	0...1	2,5	G 1/8" -28
RMM 40-1.6-1/8 H	40	0...1,6	2,5	G 1/8" -28
RMM 40-2.5-1/8 H	40	0...2,5	2,5	G 1/8" -28
RMM 40-4-1/8 H	40	0...4	2,5	G 1/8" -28
RMM 40-6-1/8 H	40	0...6	2,5	G 1/8" -28
RMM 40-10-1/8 H	40	0...10	2,5	G 1/8" -28
RMM 40-16-1/8 H	40	0...16	2,5	G 1/8" -28
RMM 40-25-1/8 H	40	0...25	2,5	G 1/8" -28
RMM 40-40-1/8 H	40	0...40	2,5	G 1/8" -28
RMM 40-60-1/8 H	40	0...60	2,5	G 1/8" -28
RMM 40-100-1/8 H	40	0...100	2,5	G 1/8" -28
RMM 40-160-1/8 H	40	0...160	2,5	G 1/8" -28
RMM 40-250-1/8 H	40	0...250	2,5	G 1/8" -28
RMM 40-315-1/8 H	40	0...315	2,5	G 1/8" -28
RMM 40-400-1/8 H	40	0...400	2,5	G 1/8" -28
RMM 40-1 H	40	0...1	2,5	G 1/4" -19
RMM 40-1.6 H	40	0...1,6	2,5	G 1/4" -19
RMM 40-2.5 H	40	0...2,5	2,5	G 1/4" -19
RMM 40-4 H	40	0...4	2,5	G 1/4" -19
RMM 40-6 H	40	0...6	2,5	G 1/4" -19
RMM 40-10 H	40	0...10	2,5	G 1/4" -19
RMM 40-16 H	40	0...16	2,5	G 1/4" -19
RMM 40-25 H	40	0...25	2,5	G 1/4" -19
RMM 40-40 H	40	0...40	2,5	G 1/4" -19
RMM 40-60 H	40	0...60	2,5	G 1/4" -19
RMM 40-100 H	40	0...100	2,5	G 1/4" -19
RMM 40-160 H	40	0...160	2,5	G 1/4" -19
RMM 40-250 H	40	0...250	2,5	G 1/4" -19
RMM 40-315 H	40	0...315	2,5	G 1/4" -19
RMM 40-400 H	40	0...400	2,5	G 1/4" -19