

属性

接口 1 + 2	BSP内螺纹,圆柱形
温度 min.	0 °C
温度 max.	120 °C
原料	黄铜 OT 58, 钢制手柄



提示

压力值适用于0 °C至+ 25 °C的温度;温度更高时请注意压力降跌。

订购指南

其他压力值和温度值承索提供。

货品

名称	DN*	尺寸	工作压力 (bar)	G1 - G2	L (mm)
MF 06 MG	6	4	16,0	G 1/4" -19	33
MF 10 MG	10	6	16,0	G 3/8" -19	41
MF 13 MG	12	8	16,0	G 1/2" -14	36
MF 20 MG	19	12	16,0	G 3/4" -14	39
MF 25 MG	25	16	16,0	G 1" -11	43
MF 32 MG	31	20	16,0	G 1.1/4" -11	48
MF 40 MG	38	24	16,0	G 1.1/2" -11	52
MF 50 MG	51	32	16,0	G 2" -11	57
MF 65 MG	60	40	16,0	G 2.1/2" -11	65
MF 75 MG	76	48	16,0	G 3" -11	75
MF 100 MG	100	64	16,0	G 4" -11	84

DN = 额定直径, 额定宽度 - G1 + G2 = 接口1+2螺纹

产品变体

MF VA 套筒滑阀, 不锈钢