


属性	
接口 1 + 2	SAE法兰
密封形式 1 + 2	用SF-O形圈扁平密封
开关路径	0°; 90°
温度 min.	-10 °C
温度 max.	80 °C
原料	锻钢制壳体 钢制球和开关轴 POM材料球形密封 NBR材料O形圈
表面保护	氧化处理





提示

请遵守球阀的操作指示。

请遵守连接元件允许的压力值。

货品

DN*	压力系列	法兰大小	LW	压力 PN	SW	SF*
			(mm)		(mm)	
31	3000 PSI	1.1/4"	32,0	250 bar	17	1,5
38	3000 PSI	1.1/2"	38,0	200 bar	17	1,5
51	3000 PSI	2"	47,5	200 bar	17	1,5
31	6000 PSI	1.1/4"	32,0	400 bar	17	1,5
38	6000 PSI	1.1/2"	38,0	400 bar	17	1,5
51	6000 PSI	2"	47,5	400 bar	17	1,5
	31 38 51 31 38	31 3000 PSI 38 3000 PSI 51 3000 PSI 31 6000 PSI 38 6000 PSI	31 3000 PSI 1.1/4" 38 3000 PSI 1.1/2" 51 3000 PSI 2" 31 6000 PSI 1.1/4" 38 6000 PSI 1.1/2"	(mm) 31 3000 PSI 1.1/4" 32,0 38 3000 PSI 1.1/2" 38,0 51 3000 PSI 2" 47,5 31 6000 PSI 1.1/4" 32,0 38 6000 PSI 1.1/2" 38,0	(mm) 31 3000 PSI 1.1/4" 32,0 250 bar 38 3000 PSI 1.1/2" 38,0 200 bar 51 3000 PSI 2" 47,5 200 bar 31 6000 PSI 1.1/4" 32,0 400 bar 38 6000 PSI 1.1/2" 38,0 400 bar	(mm) (mm) 31 3000 PSI 1.1/4" 32,0 250 bar 17 38 3000 PSI 1.1/2" 38,0 200 bar 17 51 3000 PSI 2" 47,5 200 bar 17 31 6000 PSI 1.1/4" 32,0 400 bar 17 38 6000 PSI 1.1/2" 38,0 400 bar 17

DN = 额定直径、额定宽度 - LW = 净宽 - PN = 额定压力 PB = 最大工作压力 - SW = 对应边宽度 - SF = 安全系数

备件

M 11	
BK GEKR GRIFF SW	球阀用手柄(曲柄状)
BK ANSCHLAG	球阀止挡片