

NRS (15 mm)

支撑卡圈

属性

| | |
|--------|-------------|
| 应用范围 | 用于管、软管和线缆固定 |
| 结构类型 | 管卡圈 |
| 结构类型补充 | 带橡胶型材 |
| 标准 | DIN 3016 |
| 原料 | 钢 |
| 表面保护 | 镀锌 |



提示

橡胶型材缓冲震动和打击并防止擦刮。

货品

| 名称 | 最小Ø (mm) | 浮动范围 (mm) | 孔Ø (mm) |
|-----------|-------------|--------------|------------|
| NRS 05-15 | 5 | 15,0 | 6,4 |
| NRS 06-15 | 6 | 15,0 | 6,4 |
| NRS 07-15 | 7 | 15,0 | 6,4 |
| NRS 08-15 | 8 | 15,0 | 6,4 |
| NRS 09-15 | 9 | 15,0 | 6,4 |
| NRS 10-15 | 10 | 15,0 | 6,4 |
| NRS 11-15 | 11 | 15,0 | 6,4 |
| NRS 12-15 | 12 | 15,0 | 6,4 |
| NRS 13-15 | 13 | 15,0 | 6,4 |
| NRS 14-15 | 14 | 15,0 | 6,4 |
| NRS 15-15 | 15 | 15,0 | 6,4 |
| NRS 16-15 | 16 | 15,0 | 6,4 |
| NRS 17-15 | 17 | 15,0 | 6,4 |
| NRS 18-15 | 18 | 15,0 | 6,4 |
| NRS 19-15 | 19 | 15,0 | 6,4 |
| NRS 20-15 | 20 | 15,0 | 6,4 |
| NRS 21-15 | 21 | 15,0 | 6,4 |
| NRS 22-15 | 22 | 15,0 | 6,4 |
| NRS 23-15 | 23 | 15,0 | 6,4 |
| NRS 24-15 | 24 | 15,0 | 6,4 |
| NRS 25-15 | 25 | 15,0 | 6,4 |
| NRS 26-15 | 26 | 15,0 | 6,4 |
| NRS 27-15 | 27 | 15,0 | 6,4 |
| NRS 28-15 | 28 | 15,0 | 6,4 |
| NRS 29-15 | 29 | 15,0 | 6,4 |
| NRS 30-15 | 30 | 15,0 | 6,4 |
| NRS 31-15 | 31 | 15,0 | 6,4 |
| NRS 32-15 | 32 | 15,0 | 6,4 |
| NRS 33-15 | 33 | 15,0 | 6,4 |
| NRS 34-15 | 34 | 15,0 | 6,4 |
| NRS 35-15 | 35 | 15,0 | 6,4 |
| NRS 36-15 | 36 | 15,0 | 6,4 |
| NRS 37-15 | 37 | 15,0 | 6,4 |
| NRS 38-15 | 38 | 15,0 | 6,4 |
| NRS 39-15 | 39 | 15,0 | 6,4 |
| NRS 40-15 | 40 | 15,0 | 6,4 |
| NRS 48-15 | 48 | 15,0 | 6,4 |
| NRS 75-15 | 75 | 15,0 | 6,4 |

产品变体

| | |
|----------------|-----------------------|
| NRS W4 (15 mm) | 支撑卡圈, 铬镍钢 (1.4301) |
| NRS (9 mm) | 支撑卡圈, 钢 |
| NRS (12 mm) | 支撑卡圈, 钢 |
| NRS W4 (12 mm) | 支撑卡圈, 铬镍钢 (1.4301) |

