

# NRS W4 (15 mm)

## 支撑卡圈

### 属性

应用范围	用于管、软管和线缆固定
结构类型	管卡圈
结构类型补充	带橡胶型材
标准	DIN 3016
原料	铬镍钢(1.4301)



### 货品

名称	最小Ø (mm)	浮动范围 (mm)	孔Ø (mm)
NRS 05-15 W4	5	15,0	6,4
NRS 06-15 W4	6	15,0	6,4
NRS 07-15 W4	7	15,0	6,4
NRS 08-15 W4	8	15,0	6,4
NRS 09-15 W4	9	15,0	6,4
NRS 10-15 W4	10	15,0	6,4
NRS 11-15 W4	11	15,0	6,4
NRS 12-15 W4	12	15,0	6,4
NRS 13-15 W4	13	15,0	6,4
NRS 14-15 W4	14	15,0	6,4
NRS 15-15 W4	15	15,0	6,4
NRS 16-15 W4	16	15,0	6,4
NRS 17-15 W4	17	15,0	6,4
NRS 18-15 W4	18	15,0	6,4
NRS 19-15 W4	19	15,0	6,4
NRS 20-15 W4	20	15,0	6,4
NRS 21-15 W4	21	15,0	6,4
NRS 22-15 W4	22	15,0	6,4
NRS 23-15 W4	23	15,0	6,4
NRS 24-15 W4	24	15,0	6,4
NRS 25-15 W4	25	15,0	6,4
NRS 26-15 W4	26	15,0	6,4
NRS 27-15 W4	27	15,0	6,4
NRS 28-15 W4	28	15,0	6,4
NRS 29-15 W4	29	15,0	6,4
NRS 30-15 W4	30	15,0	6,4
NRS 31-15 W4	31	15,0	6,4
NRS 32-15 W4	32	15,0	6,4
NRS 33-15 W4	33	15,0	6,4
NRS 34-15 W4	34	15,0	6,4
NRS 35-15 W4	35	15,0	6,4
NRS 36-15 W4	36	15,0	6,4
NRS 37-15 W4	37	15,0	6,4
NRS 38-15 W4	38	15,0	6,4
NRS 39-15 W4	39	15,0	6,4
NRS 40-15 W4	40	15,0	6,4

### 产品变体

NRS (15 mm)	支撑卡圈, 钢
NRS (9 mm)	支撑卡圈, 钢
NRS (12 mm)	支撑卡圈, 钢
NRS W4 (12 mm)	支撑卡圈, 铬镍钢 (1.4301)
NRS (20 mm)	支撑卡圈, 钢
NRS W4 (20 mm)	支撑卡圈, 铬镍钢 (1.4301)
NRS (25 mm)	支撑卡圈, 钢