

NRS (25 mm)

支撑卡圈

属性

应用范围	用于管、软管和线缆固定
结构类型	管卡圈
结构类型补充	带橡胶型材
标准	DIN 3016
原料	钢
表面保护	镀锌



提示

橡胶型材缓冲震动和打击并防止擦刮。

货品

名称	最小Ø (mm)	浮动范围 (mm)	孔Ø (mm)
NRS 15-25	15	25,0	10,5
NRS 22-25	22	25,0	10,5
NRS 30-25	30	25,0	10,5
NRS 38-25	38	25,0	10,5
NRS 42-25	42	25,0	10,5
NRS 45-25	45	25,0	10,5
NRS 46-25	46	25,0	10,5
NRS 50-25	50	25,0	10,5
NRS 55-25	55	25,0	10,5
NRS 60-25	60	25,0	10,5
NRS 65-25	65	25,0	10,5
NRS 67-25	67	25,0	10,5
NRS 68-25	68	25,0	10,5
NRS 70-25	70	25,0	10,5
NRS 72-25	72	25,0	10,5
NRS 74-25	74	25,0	10,5
NRS 125-25	125	25,0	10,5

产品变体

NRS (9 mm)	支撑卡圈, 钢
NRS (12 mm)	支撑卡圈, 钢
NRS W4 (12 mm)	支撑卡圈, 铬镍钢(1.4301)
NRS (15 mm)	支撑卡圈, 钢
NRS W4 (15 mm)	支撑卡圈, 铬镍钢(1.4301)
NRS (20 mm)	支撑卡圈, 钢
NRS W4 (20 mm)	支撑卡圈, 铬镍钢(1.4301)