

# NRS (25 mm)

## 支撑卡圈

### 属性

|        |             |
|--------|-------------|
| 应用范围   | 用于管、软管和线缆固定 |
| 结构类型   | 管卡圈         |
| 结构类型补充 | 带橡胶型材       |
| 标准     | DIN 3016    |
| 原料     | 钢           |
| 表面保护   | 镀锌          |



### 提示

橡胶型材缓冲震动和打击并防止擦刮。

### 货品

| 名称         | 最小Ø<br>(mm) | 浮动范围<br>(mm) | 孔Ø<br>(mm) |
|------------|-------------|--------------|------------|
| NRS 15-25  | 15          | 25,0         | 10,5       |
| NRS 22-25  | 22          | 25,0         | 10,5       |
| NRS 30-25  | 30          | 25,0         | 10,5       |
| NRS 38-25  | 38          | 25,0         | 10,5       |
| NRS 42-25  | 42          | 25,0         | 10,5       |
| NRS 45-25  | 45          | 25,0         | 10,5       |
| NRS 46-25  | 46          | 25,0         | 10,5       |
| NRS 50-25  | 50          | 25,0         | 10,5       |
| NRS 55-25  | 55          | 25,0         | 10,5       |
| NRS 60-25  | 60          | 25,0         | 10,5       |
| NRS 65-25  | 65          | 25,0         | 10,5       |
| NRS 67-25  | 67          | 25,0         | 10,5       |
| NRS 68-25  | 68          | 25,0         | 10,5       |
| NRS 70-25  | 70          | 25,0         | 10,5       |
| NRS 72-25  | 72          | 25,0         | 10,5       |
| NRS 74-25  | 74          | 25,0         | 10,5       |
| NRS 125-25 | 125         | 25,0         | 10,5       |

### 产品变体

|                |                   |
|----------------|-------------------|
| NRS (9 mm)     | 支撑卡圈, 钢           |
| NRS (12 mm)    | 支撑卡圈, 钢           |
| NRS W4 (12 mm) | 支撑卡圈, 铬镍钢(1.4301) |
| NRS (15 mm)    | 支撑卡圈, 钢           |
| NRS W4 (15 mm) | 支撑卡圈, 铬镍钢(1.4301) |
| NRS (20 mm)    | 支撑卡圈, 钢           |
| NRS W4 (20 mm) | 支撑卡圈, 铬镍钢(1.4301) |