

# SBS 220 / 225

夹爪卡圈

**HANSA FLEX**

## 属性

应用范围	用于橡胶和塑料软管
结构类型	软管卡圈
结构类型补充	2件,夹爪拧紧力按照DIN 3017
原料	钢
表面保护	电镀涂层



## 货品

名称	最小Ø (mm)	浮动范围 (mm)
SBS 220-42	42	20,0
SBS 220-44	44	20,0
SBS 220-46	46	20,0
SBS 220-48	48	20,0
SBS 220-50	50	20,0
SBS 220-52	52	20,0
SBS 220-54	54	20,0
SBS 220-56	56	20,0
SBS 220-58	58	20,0
SBS 220-60	60	20,0
SBS 220-62	62	20,0
SBS 220-64	64	20,0
SBS 220-66	66	20,0
SBS 220-68	68	20,0
SBS 220-70	70	20,0
SBS 220-72	72	20,0
SBS 220-74	74	20,0
SBS 220-76	76	20,0
SBS 220-78	78	20,0
SBS 220-80	80	20,0
SBS 220-82	82	20,0
SBS 220-84	84	20,0
SBS 220-86	86	20,0
SBS 220-88	88	20,0
SBS 220-90	90	20,0
SBS 220-92	92	20,0
SBS 220-94	94	20,0
SBS 220-96	96	20,0
SBS 220-98	98	20,0
SBS 220-100	100	20,0
SBS 225-42	42	25,0
SBS 225-44	44	25,0
SBS 225-46	46	25,0
SBS 225-48	48	25,0
SBS 225-50	50	25,0
SBS 225-52	52	25,0
SBS 225-54	54	25,0
SBS 225-56	56	25,0
SBS 225-58	58	25,0
SBS 225-60	60	25,0
SBS 225-62	62	25,0
SBS 225-64	64	25,0
SBS 225-66	66	25,0
SBS 225-68	68	25,0
SBS 225-70	70	25,0
SBS 225-72	72	25,0
SBS 225-74	74	25,0
SBS 225-76	76	25,0
SBS 225-78	78	25,0
SBS 225-80	80	25,0



尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。

06.06.2026

HANSA-FLEX AG

[www.hansa-flex.com](http://www.hansa-flex.com)

1

# SBS 220 / 225

夹爪卡圈

## 货品

名称	最小Ø (mm)	浮动范围 (mm)
SBS 225-82	82	25,0
SBS 225-84	84	25,0
SBS 225-86	86	25,0
SBS 225-88	88	25,0
SBS 225-90	90	25,0
SBS 225-92	92	25,0
SBS 225-94	94	25,0
SBS 225-96	96	25,0
SBS 225-98	98	25,0
SBS 225-100	100	25,0