

SRS 1-5 D PP

管卡圈,双管

HANSA FLEX

属性

| | |
|---------|------------|
| 结构类型 | 双管卡圈 |
| 结构类型补充 | 卡圈内壁带槽 |
| 标准 | DIN 3015-3 |
| 温度 min. | -30 °C |
| 温度 max. | 90 °C |
| 原料 | 聚丙烯 |



提示

对软管和线缆的支撑推荐使用内表面光滑的卡圈。装配则不带预张力,从而使块高H减小间隙大小S1。

描述

卡圈内部的槽可起到缓冲打击和震动的作用,可吸纳管的轴向力。半部之间的间隙起到预张管子的作用。

订购指南

1 件 = 2个卡圈半部

货品

| 名称 | 卡圈大小 | 管外径 Ø d2 (mm) | 管外径 Ø d2 | a (mm) | B (mm) | H (mm) | L (mm) | S1 (mm) |
|----------------|------|------------------|----------|-----------|-----------|-----------|-----------|------------|
| SRS 106 D PP | 1 | 6,0 | - | 20 | 30 | 27 | 36 | 1,0 |
| SRS 106.4 D PP | 1 | 6,4 | 1/4" | 20 | 30 | 27 | 36 | 1,0 |
| SRS 108 D PP | 1 | 8,0 | 5/16" | 20 | 30 | 27 | 36 | 1,0 |
| SRS 109.5 D PP | 1 | 9,5 | 3/8" | 20 | 30 | 27 | 36 | 1,0 |
| SRS 110 D PP | 1 | 10,0 | - | 20 | 30 | 27 | 36 | 1,0 |
| SRS 112 D PP | 1 | 12,0 | - | 20 | 30 | 27 | 36 | 1,0 |
| SRS 212.7 D PP | 2 | 12,7 | 1/2" | 29 | 30 | 26 | 53 | 1,2 |
| SRS 213.5 D PP | 2 | 13,5 | - | 29 | 30 | 26 | 53 | 1,2 |
| SRS 214 D PP | 2 | 14,0 | - | 29 | 30 | 26 | 53 | 1,2 |
| SRS 215 D PP | 2 | 15,0 | - | 29 | 30 | 26 | 53 | 1,2 |
| SRS 216 D PP | 2 | 16,0 | 5/8" | 29 | 30 | 26 | 53 | 1,2 |
| SRS 217.2 D PP | 2 | 17,2 | - | 29 | 30 | 26 | 53 | 1,2 |
| SRS 218 D PP | 2 | 18,0 | - | 29 | 30 | 26 | 53 | 1,2 |
| SRS 319 D PP | 3 | 19,0 | 3/4" | 36 | 30 | 37 | 67 | 1,6 |
| SRS 320 D PP | 3 | 20,0 | - | 36 | 30 | 37 | 67 | 1,6 |
| SRS 321.3 D PP | 3 | 21,3 | - | 36 | 30 | 37 | 67 | 1,6 |
| SRS 322 D PP | 3 | 22,0 | - | 36 | 30 | 37 | 67 | 1,6 |
| SRS 325 D PP | 3 | 25,0 | 1" | 36 | 30 | 37 | 67 | 1,6 |
| SRS 426.9 D PP | 4 | 26,9 | - | 45 | 30 | 42 | 82 | 2,0 |
| SRS 428 D PP | 4 | 28,0 | - | 45 | 30 | 42 | 82 | 2,0 |
| SRS 430 D PP | 4 | 30,0 | - | 45 | 30 | 42 | 82 | 2,0 |
| SRS 532 D PP | 5 | 32,0 | 1.1/4" | 56 | 30 | 54 | 106 | 2,0 |
| SRS 533.7 D PP | 5 | 33,7 | - | 56 | 30 | 54 | 106 | 2,0 |
| SRS 535 D PP | 5 | 35,0 | - | 56 | 30 | 54 | 106 | 2,0 |
| SRS 538 D PP | 5 | 38,0 | 1.1/2" | 56 | 30 | 54 | 106 | 2,0 |
| SRS 542 D PP | 5 | 42,0 | - | 56 | 30 | 54 | 106 | 2,0 |

产品变体

| | |
|----------------|---------------|
| SRS 1-5 D PP G | 管卡圈,双管,卡圈内壁光滑 |
| SRS 1-5 D PA | 管卡圈,双管,卡圈内壁带槽 |
| SRS 1-5 D VG | 管卡圈,双管,卡圈内壁光滑 |

是以下产品的附加元件

| | |
|-----|-----------|
| B A | B类组装 表面安装 |
| B | B类组装 |