

SRS 1-6 SPW V4

弯角式焊接和螺旋板

HANSA FLEX

属性

| | |
|------|------------|
| 结构形式 | 角度90° |
| 结构类型 | 单管卡圈用 |
| 结构系列 | 轻 |
| 标准 | DIN 3015-1 |
| 原料 | 不锈钢 1.4571 |



货品

| 名称 | 卡圈大小 | B (mm) | c (mm) | e1 (mm) | e2 (mm) | G | H (mm) | L (mm) | S (mm) |
|----------------|------|-----------|-----------|------------|------------|-----|-----------|-----------|-----------|
| SRS SPW 1 A V4 | 1 | 30 | 6,6 | 20,0 | 20 | M 6 | 30 | 36,0 | 3 |
| SRS SPW 2 V4 | 2 | 30 | 6,6 | 26,0 | 26 | M 6 | 30 | 42,0 | 3 |
| SRS SPW 3 V4 | 3 | 30 | 6,6 | 33,0 | 33 | M 6 | 30 | 50,0 | 3 |
| SRS SPW 4 V4 | 4 | 30 | 6,6 | 40,0 | 40 | M 6 | 30 | 59,0 | 3 |
| SRS SPW 5 V4 | 5 | 30 | 6,6 | 52,0 | 52 | M 6 | 30 | 72,0 | 3 |
| SRS SPW 6 V4 | 6 | 30 | 6,6 | 66,0 | 66 | M 6 | 30 | 88,0 | 3 |

产品变体

SRS 1-6 SPW 弯角式焊接和螺旋板, 钢