


属性

工作压力 最大700巴





描述

用于用NPT接口安装压力表

A	В	С	ØD	ØE	ØF	重量
(mm)	(mm)	(mm)				(kg)
71	32	32	3/8"	3/8" NPT	1/2"	0,9
117	40	32	3/8"	3/8" NPT	1/4"	0,9
155	35	32	3/8"	3/8" NPT	1/2"	0,9
71	31	32	3/8"	3/8" NPT	1/4"	0,9
	71 117	71 32 117 40 155 35	71 32 32 117 40 32 155 35 32	(mm) (mm) (mm) 71 32 32 3/8" 117 40 32 3/8" 155 35 32 3/8"	(mm) (mm) (mm) 71 32 32 3/8" 3/8" NPT 117 40 32 3/8" 3/8" NPT 155 35 32 3/8" 3/8" NPT	(mm) (mm) 71 32 32 3/8" NPT 1/2" 117 40 32 3/8" 3/8" NPT 1/4" 155 35 32 3/8" 3/8" NPT 1/2"

附件	
NY 2100	热塑性塑料最高压软管
GKS	橡胶弯折保护
PNY 2100 HN	压力内接头,AGN
PHY 2100	压力卡套 NY 2100
SKL HN SP	螺旋接合器活动半部
SKL ZUBS SP	用于 SKLSP 的防尘保护
SKF IN SP	螺旋接合器固定半部
SKF ZUBS SP	用于 SKFSP 的防尘保护