


属性

规格

钢规格,带精密阀杆 suitable for control panel installation

工作压力 达 400 巴





提示

这些阀门必须根据具体应用进行调节。

描述

一个流量方向的精确的体积流量调节及阻断,反方向自由流量

无渗漏金属密封,线性开口横截面

大流量范围中精确的节流

止回阀开口压力0.35巴 调节方法与节流阀相同

调节钮中的内六角螺钉用于止动

可提供一个附加的防松螺母用于配电板安装

华	
ш	пп

流量 max. (L/min) 8	压力 (bar) 400	A (mm) 50	B (mm) 64	C (mm)	D (mm)	螺纹	重量 (kg)
8	400	. ,		, ,			(kg)
		50	64	40			
14			04	16	13,5	G 1/8"	0,13
	400	66	78	20	17,0	G 1/4"	0,25
38	400	79	93	25	19,5	G 3/8"	0,50
50	400	95	107	30	21,0	G 1/2"	0,75
80	400	115	132	40	26,5	G 3/4"	1,60
190	320	139	167	50	35,0	G 1"	3,05
200	320	157	172	55	35,0	G 1.1/4"	3,75
350	320	190	181	65	35,0	G 1.1/2"	5,76
450	320	228	202	75	44,0	G 2"	10,00
	38 50 80 190 200 350	38 400 50 400 80 400 190 320 200 320 350 320	38 400 79 50 400 95 80 400 115 190 320 139 200 320 157 350 320 190	38 400 79 93 50 400 95 107 80 400 115 132 190 320 139 167 200 320 157 172 350 320 190 181	38 400 79 93 25 50 400 95 107 30 80 400 115 132 40 190 320 139 167 50 200 320 157 172 55 350 320 190 181 65	38 400 79 93 25 19,5 50 400 95 107 30 21,0 80 400 115 132 40 26,5 190 320 139 167 50 35,0 200 320 157 172 55 35,0 350 320 190 181 65 35,0	38 400 79 93 25 19,5 G 3/8" 50 400 95 107 30 21,0 G 1/2" 80 400 115 132 40 26,5 G 3/4" 190 320 139 167 50 35,0 G 1" 200 320 157 172 55 35,0 G 1.1/4" 350 320 190 181 65 35,0 G 1.1/2"

Δp=20巴时最大流速值

附件

HK KM 202 防松螺母