


属性	
规格	直动式
工作压力	最大350巴





提示

这些阀门必须根据具体应用进行调节

描述

nur einstellbar, wenn Druck an Anschluss 1 < 50bar 接口2处可以施加最大压力 响应时间约为2毫秒

货品

调节范围 min.	调节范围 max.	Qmax	Α	В	所分配的旋入式壳体	旋入式螺 纹	SW	拧紧扭 矩	重量
(bar)	(bar)	(L/min)	(mm)	(mm)			(mm)	(N-m)	(kg)
35	210	95	61,0	40,0	HK FAU / HK FAUS	T-10A	22	50,0	0,5
55	315	95	61,0	40,0	HK FAU / HK FAUS	T-10A	22	50,0	0,5
35	210	200	64,0	48,0	HK CAV / HK CAVS / HK CAW / HK CAWS	T-3A	28	65,0	0,5
55	315	200	64,0	48,0	HK CAV / HK CAVS / HK CAW / HK CAWS	T-3A	28	65,0	0,5
	min. (bar) 35 55 35	min. max. (bar) 35 210 55 315 35 210	min. max. (bar) (bar) 35 210 55 315 35 210 200	min. max. (L/min) (mm) 35 210 95 61,0 55 315 95 61,0 35 210 200 64,0	min. (bar) max. (bar) (L/min) (mm) (mm) 35 210 95 61,0 40,0 55 315 95 61,0 40,0 35 210 200 64,0 48,0	min. (bar) max. (bar) (L/min) (mm) (mm) 35 210 95 61,0 40,0 HK FAU / HK FAUS 55 315 95 61,0 40,0 HK FAU / HK FAUS 35 210 200 64,0 48,0 HK CAV / HK CAVS / HK CAW / HK CAWS	min. (bar) max. (bar) (L/min) (mm) (mm)<	min. (bar) max. (bar) (L/min) (mm) (mm)<	min. (bar) max. (bar) 技術 技術 技術 技術 技術 大学 (N-m) (N-m) (N-m) 35 210 95 61,0 40,0 HK FAU / HK FAUS T-10A 22 50,0 55 315 95 61,0 40,0 HK FAU / HK FAUS T-10A 22 50,0 35 210 200 64,0 48,0 HK CAV / HK CAW / HK CAW / HK CAWS T-3A 28 65,0

附件	
HK GEH CA	螺纹插装阀的阀壳体T-3A
HK GEH FA	螺纹插装阀 T-10A
HK HR SUN	用于螺纹插装阀的手轮 SUN