



属性	
结构类型	杆环槽圈
工作压力	达 400 巴
滑动速度 max.	0,5 m/s
规格	米制的
温度 min.	-30 °C
温度 max.	80 °C
适用介质	矿物油.
装配	在闭合环槽A内 在开放环槽B内
原料	PUR
应用	液压





描述

摩擦很少的密封件.

高抗磨损强度

简单的解决方案.

订购指南

我们可以短时间内完成20至510毫米直径EU密封件的加工。

货品					
名称	D	d	L	槽按照	
TU 00 40 4	(mm)	(mm)	(mm)		
EU 06 12-1	12,0	6	5,8	-	
EU 06 14	14,0	6	6,3	ISO 5597	
EU 08 14-1	14,4	8	10,5	-	
EU 08 16	16,0	8	6,3	ISO 5597	
EU 08 18-1	18,0	8	9,0		
EU 10 18	18,0	10	6,3	ISO 5597	
EU 10 20	20,0	10	8,0	ISO 5597	
EU 12 17	17,0	12	4,0		
EU 12 20-1	20,0	12	5,5	-	
EU 12 20	20,0	12	6,3	ISO 5597	
EU 12 22	22,0	12	8,0	ISO 5597	
EU 12 22-1	22,0	12	9,0	-	
EU 14 22	22,0	14	6,3	ISO 5597	
EU 14 24	24,0	14	8,0	-	
EU 15 23-1	23,0	15	6,3	-	
EU 15 25-1	25,0	15	9,0	-	
EU 16 21	20,6	16	3,6	-	
EU 16 22	22,0	16	6,0	-	
EU 16 24	24,0	16	6,3	-	
EU 16 24-1	24,0	16	7,0	-	
EU 16 26	26,0	16	8,0	ISO 5597	
EU 16 26-2	26,0	16	10,0	-	
EU 18 24	24,0	18	5,2	-	
EU 18 24-1	24,0	18	6,0	-	
EU 18 26-1	26,0	18	6,3	ISO 5597	
EU 18 26	26,0	18	9,0	-	
EU 18 28	28,0	18	8,0	ISO 5597	
EU 18 28-1	28,0	18	9,0	-	
EU 20 26-1	26,0	20	5,5	-	
EU 20 28	28,0	20	6,3	ISO 5597	
EU 20 28-1	28,0	20	7,0	-	
EU 20 28-2	28,0	20	8,0	-	
EU 20 30	30,0	20	8,0	ISO 5597	
EU 20 30-2	30,0	20	9,0	-	
EU 20 35	35,0	20	11,0	-	
EU 22 30-1	30,0	22	6,3	ISO 5597	
EU 22 30	30,0	22	9,0	-	
	•		· · · · · · · · · · · · · · · · · · ·		—





货品				
名称	D	d	Ļ	槽按照
EU 22 32-1	(mm) 32,0	(mm) 22	(mm) 8,0	ISO 5597
EU 22 32	32,0	22	10,0	-
EU 24 34	34,0	24	8,0	-
EU 24 34-1	34,0	24	9,5	-
EU 25 32	32,0	25	7,0	-
EU 25 33	33,0	25	6,3	-
EU 25 33-3	33,0	25	7,0	-
EU 25 33-1 EU 25 33-2	33,0 33,0	25 25	8,0 11,0	-
EU 25 35-2	35,0	25	8,0	ISO 5597
EU 25 38-1	38,0	25	10,0	-
EU 25 40	40,0	25	11,0	-
EU 28 36	36,0	28	6,3	-
EU 28 38	38,0	28	8,0	ISO 5597
EU 28 38-1	38,0	28	9,0	-
EU 28 38-2	38,0	28	11,0	-
EU 28 40	40,0	28	9,5	-
EU 28 43	43,0	28	12,5	ISO 5597
EU 30 38	38,0	30	6,3	
EU 30 38-1	38,0	30	9,0	-
EU 30 40-3 EU 30 40	40,0 40,0	30	6,3	-
EU 30 40-1	40,0	30	8,0 11,0	-
EU 30 43	43,0	30	10,0	<u> </u>
EU 30 45-1	45,0	30	9,0	-
EU 32 40-1	40,0	32	6,3	-
EU 32 40	40,0	32	9,0	-
EU 32 42	42,0	32	8,0	ISO 5597
EU 32 42-1	42,0	32	11,0	-
EU 32 45	45,0	32	11,0	-
EU 33 43-1	43,0	33	11,0	-
EU 32 47-1	47,0	32	11,0	-
EU 35 43	43,0	35	6,3	-
EU 35 43-1	43,0	35	9,0	-
EU 35 45 EU 35 45-1	45,0 45,0	35 35	8,0 11,0	-
EU 35 45-1	45,0	35	13,5	<u> </u>
EU 35 46	46,0	35	9,0	<u> </u>
EU 35 46-1	46,0	35	10,0	-
EU 35 47	47,0	35	9,0	-
EU 35 50	50,0	35	11,0	-
EU 36 44	44,0	36	9,0	-
EU 36 46	46,0	36	8,0	ISO 5597
EU 36 46-1	46,0	36	11,0	-
EU 36 48-1	48,0	36	8,0	-
EU 36 48	48,0	36	9,0	-
EU 36 51	51,0	36	11,0	- ICO 5507
EU 36 51-1 EU 37 45	51,0 45,0	36 37	12,5 6,3	ISO 5597 -
EU 38 44	44,0	38	5,3	-
EU 38 45	45,0	38	5,5	-
EU 38 45-1	45,0	38	7,0	
EU 39 50	50,0	39	11,0	-
EU 40 48	48,0	40	6,3	-
EU 40 48-1	48,0	40	9,0	-
EU 40 50-2	50,0	40	8,0	ISO 5597
EU 40 50	50,0	40	10,0	-
EU 40 50-1	50,0	40	11,0	-
EU 40 50-3	50,0	40	13,5	-
EU 40 52	52,0	40	9,0	-
EU 40 55	55,0 55,0	40 40	11,0	- ISO 5507
EU 40 55-1 EU 40 60	55,0 60.0	40	12,5 13,0	ISO 5597
EU 40 00	60,0	40	13,0	-





货品				
名称	D	d	L	
EU 40.00.4	(mm)	(mm)	(mm)	
EU 42 62-1 EU 45 53	62,0 53,0	42 45	11,0 6,3	<u>-</u>
EU 45 53-2	53,0	45	11,0	-
EU 45 53-1	53,0	45	13,0	-
EU 45 55-1	55,0	45	8,0	ISO 5597
EU 45 55	55,0	45	11,0	-
EU 45 58-1	58,0	45	10,0	-
EU 45 60	60,0	45	11,0	-
EU 45 60-1	60,0	45	12,5	ISO 5597
EU 45 65-2 EU 45 65	65,0 65,0	45 45	11,0 13,0	-
EU 45 65-1	65,0	45	14,5	-
EU 46 56	56,0	46	8,0	-
EU 50 60-1	60,0	50	8,0	
EU 50 60	60,0	50	11,0	-
EU 50 60-2	60,0	50	13,0	-
EU 50 65-1	65,0	50	11,0	-
EU 50 65	65,0	50	12,5	ISO 5597
EU 50 68-1	68,0	50	10,0	-
EU 50 70	70,0	50	13,0	<u>-</u>
EU 52 62	62,0	52	11,0	-
EU 55 63-1 EU 55 65	63,0 65,0	55 55	13,0 8,0	-
EU 55 65-1	65,0	55	11,0	-
EU 55 65-2	65,0	55	13,0	<u>-</u>
EU 55 65-3	65,0	55	14,5	_
EU 55 67-1	67,0	55	11,0	-
EU 55 68	68,0	55	11,0	-
EU 55 70	70,0	55	11,0	-
EU 55 70-1	70,0	55	13,0	-
EU 55 75	75,0	55	13,0	-
EU 55 75-1	75,0	55	14,5	-
EU 56 66 EU 56 71	66,0	56	11,0	-
EU 56 71-1	71,0 71,0	56 56	11,0 12,5	-
EU 56 76	76,0	56	13,0	<u>-</u>
EU 56 76-1	76,0	56	14,5	_
EU 56 76-2	76,0	56	16,0	ISO 5597
EU 60 70-1	70,0	60	8,0	-
EU 60 70	70,0	60	11,0	-
EU 60 70-S	70,0	60	15,0	
EU 60 72	72,0	60	9,0	-
EU 60 72-1	72,0	60	10,0	-
EU 60 75 EU 60 75-1	75,0	60	11,0	-
EU 60 75-1	75,0 77,0	60 60	13,0 12,0	-
EU 60 80	80,0	60	13,0	<u>-</u>
EU 61 69-1	69,0	61	8,5	<u> </u>
EU 62 74-1	74,0	62	14,0	_
EU 63 73-1	73,0	63	11,0	-
EU 63 73	73,0	63	13,0	-
EU 63 75	75,0	63	9,6	-
EU 63 78-1	78,0	63	11,0	-
EU 63 78	78,0	63	12,5	ISO 5597
EU 63 83-1	83,0	63	14,5	-
EU 63 83-2	83,0	63	16,0	-
EU 65 75-3 EU 65 77-1	75,0 77,0	65 65	11,0 10,0	-
EU 65 77-1 EU 65 80	77,0 80,0	65	11,0	-
EU 65 80-1	80,0	65	13,0	<u> </u>
EU 65 85	85,0	65	13,0	-
EU 65 85-1	85,0	65	14,5	-
EU 70 80-3	80,0	70	6,5	-





			14th Laborator
D (mm)	d (mm)	L (mm)	槽按照
			_
80,0	70	11,0	-
80,0	70	13,0	-
85,0	70	11,0	-
85,0	70	12,5	ISO 5597
90,0	70	16,0	ISO 5597
		<u> </u>	-
			-
			-
			-
			-
			<u> </u>
			-
•		· · · · · · · · · · · · · · · · · · ·	-
· · · · · · · · · · · · · · · · · · ·	80		ISO 5597
90,0	80	8,0	-
90,0	80	13,0	-
92,0	80	9,6	-
95,0	80	10,0	-
95,0	80	11,0	-
95,0	80	12,5	-
95,0	80	13,0	-
· · · · · · · · · · · · · · · · · · ·			-
<u>.</u>		<u> </u>	-
<u>.</u>			-
			-
			-
			-
			ISO 5597
			-
			-
	90		ISO 5597
99,0	91	8,5	-
104,0	93	11,0	-
105,0	95	11,0	-
115,0	95	13,0	-
109,0	99	15,0	-
		15,0	-
			-
· · · · · · · · · · · · · · · · · · ·			-
			-
			- ISO 5597
			ISO 5597
			-
			<u>-</u>
		· · · · · · · · · · · · · · · · · · ·	<u>-</u>
	105	13,0	-
125,0	110	12,0	-
125,0	110	16,0	-
130,0	110	13,0	-
130,0	110	16,0	ISO 5597
135,0	115	13,0	-
130,0	120	12,5	-
130,0	120	15,0	-
			-
<u>.</u>			-
· · · · · · · · · · · · · · · · · · ·			-
140,0	120	16,0	-
145,0	125	13,0	-
	(mm) 80,0 80,0 80,0 80,0 85,0 90,0 85,0 90,0 82,5 85,0 90,0 90,0 95,0 84,0 88,0 100,0 100,0 90,0 92,0 95,0 95,0 95,0 95,0 95,0 100,0 105,0 105,0 105,0 105,0 105,0 105,0 110,0 110,0 110,0 110,0 110,0 110,0 110,0 115,0	(mm) (mm) 80,0 70 80,0 70 85,0 70 90,0 70 82,5 73 85,0 75 90,0 75 90,0 75 90,0 75 95,0 75 95,0 75 84,0 76 88,0 78 100,0 80 90,0 80 90,0 80 90,0 80 90,0 80 90,0 80 90,0 80 90,0 80 95,0 80 95,0 80 95,0 80 95,0 80 95,0 85 100,0 85 100,0 85 105,0 85 100,0 85 105,0 90 105,0 90 1	(mm) (mm) (mm) 80,0 70 8,0 80,0 70 11,0 80,0 70 13,0 85,0 70 11,0 85,0 70 12,5 90,0 70 16,0 82,5 73 8,0 85,0 75 8,0 85,0 75 13,0 90,0 75 11,0 90,0 75 13,0 90,0 75 13,0 95,0 75 13,0 95,0 75 13,0 95,0 75 13,0 95,0 75 13,0 95,0 75 13,0 95,0 80 15,0 100,0 80 16,0 90,0 80 16,0 90,0 80 8,0 90,0 80 8,0 90,0 80 13,0 95,0 80





货品				
名称	D	d	L	槽按照
	(mm)	(mm)	(mm)	
EU 125 150	150,0	125	15,0	
EU 130 140	140,0	130	8,0	
EU 130 145-2	145,0	130	15,0	
EU 130 150	150,0	130	13,0	
EU 130 150-1	150,0	130	16,0	
EU 140 150-1	150,0	140	12,5	
EU 140 160-2	160,0	140	16,0	ISO 5597
EU 140 165	165,0	140	20,0	ISO 5597
EU 141 151-S	151,0	141	15,0	-
EU 150 170-1	170,0	150	14,5	
EU 150 170-2	170,0	150	16,0	
EU 160 180	180,0	160	13,0	
EU 160 180-1	180,0	160	16,0	-
EU 160 185	185,0	160	20,0	-
EU 162 172-S	172,0	162	15,0	
EU 170 190-1	190,0	170	16,0	
EU 180 200-1	200,0	180	16,0	
EU 180 200-2	200,0	180	20,0	
EU 183 193-S	193,0	183	15,0	-
EU 190 210-1	210,0	190	16,0	-
EU 200 212-1	212,0	200	16,0	-
EU 200 220	220,0	200	13,0	-
EU 200 220-1	220,0	200	16,0	-
EU 207 217-S	217,0	207	15,0	
EU 210 230	230,0	210	13,0	
EU 210 230-2	230,0	210	16,0	
EU 210 235-1	235,0	210	26,0	
EU 220 240	240,0	220	13,0	
EU 220 240-1	240,0	220	16,0	
EU 230 250	250,0	230	13,0	
EU 230 260	260,0	230	25,0	-
EU 231 241-S	241,0	231	15,0	-
EU 240 260	260,0	240	13,0	-
EU 240 260-1	260,0	240	16,0	-
EU 240 270	270,0	240	19,0	-
EU 250 270	270,0	250	13,0	-
EU 250 270-1	270,0	250	16,0	
EU 280 305-1	305,0	280	16,0	-
EU 280 310	310,0	280	25,0	-