
HK K C E-Motor 12V

直流电动机 12V



属性	
规格	工业用直流电机
电压	12 V





Α	ØВ	规格	功率	转向	转速 max.	接通持续时间 S2 运行	接通持续时间 S3 运行	保护级 别	轴	重量
(mm)	(mm)		(kW)		(rpm)	(min)	(%)			(kg)
158,5	80,0	-	0,5	可换向	2500	5,0	17,0	IP 54	型号Y Ø15.6 x 6.5 x 10.5	2,60
215,5	112,5	带通风器	1,5	右转	2300	4,0	14,0	IP23	型号X Ø17.9 x 8.3 x 9.0	7,72
158,5	80,0	带热保护	0,8	可换向	3500	4,0	9,0	IP44	型号Y Ø15.6 x 6.5 x 10.5	2,60
173,5	114,0	_	1,6	右转	2600	3,0	7,5	IP 54	型号X Ø17.9 x 8.3 x 9.0	6,80
207,5	131,0	带热保护	2,4	右转	2600	1,0	8,0	IP 54	型号X Ø16.8 x 8.0 x 7.0	11,28
183,0	114,0	-	1,5	右转	2300	2,0	8,0	IP 54	型号X Ø17.9 x 8.3 x 9.0	7,14
173,5	114,0	带热保护	1,6	右转	2600	3,0	7,5	IP 54	型号X Ø17.9 x 8.3 x 9.0	6,70
	(mm) 158,5 215,5 158,5 173,5 207,5 183,0	(mm) (mm) 158,5 80,0 215,5 112,5 158,5 80,0 173,5 114,0 207,5 131,0 183,0 114,0	(mm) (mm) 158,5 80,0 - 215,5 112,5 带通风器 158,5 80,0 带热保护 173,5 114,0 - 207,5 131,0 带热保护 183,0 114,0 -	(mm) (mm) (kW) 158,5 80,0 - 0,5 215,5 112,5 带通风器 1,5 158,5 80,0 带热保护 0,8 173,5 114,0 - 1,6 207,5 131,0 带热保护 2,4 183,0 114,0 - 1,5	(mm) (mm) (kW) 158,5 80,0 - 0,5 可换向 215,5 112,5 带通风器 1,5 右转 158,5 80,0 带热保护 0,8 可换向 173,5 114,0 - 1,6 右转 207,5 131,0 带热保护 2,4 右转 183,0 114,0 - 1,5 右转	(mm) (mm) (kW) max. (rpm) 158,5 80,0 - 0,5 可换向 2500 215,5 112,5 带通风器 1,5 右转 2300 158,5 80,0 带热保护 0,8 可换向 3500 173,5 114,0 - 1,6 右转 2600 207,5 131,0 带热保护 2,4 右转 2600 183,0 114,0 - 1,5 右转 2300	(mm) (mm) (kW) max. (rpm) 运行 (min) 158,5 80,0 - 0,5 可换向 2500 5,0 215,5 112,5 带通风器 1,5 右转 2300 4,0 158,5 80,0 带热保护 0,8 可换向 3500 4,0 173,5 114,0 - 1,6 右转 2600 3,0 207,5 131,0 带热保护 2,4 右转 2600 1,0 183,0 114,0 - 1,5 右转 2300 2,0	(mm) (mm) (kW) max. (rpm) 运行 (%) 158,5 80,0 - 0,5 可换向 2500 5,0 17,0 215,5 112,5 带通风器 1,5 右转 2300 4,0 14,0 158,5 80,0 带热保护 0,8 可换向 3500 4,0 9,0 173,5 114,0 - 1,6 右转 2600 3,0 7,5 207,5 131,0 带热保护 2,4 右转 2600 1,0 8,0 183,0 114,0 - 1,5 右转 2300 2,0 8,0	(mm) (mm) (kW) (rpm) 运行 (min) 运行 (%) 运行 (%) 运行 (%) 158,5 80,0 - 0,5 可换向 2500 5,0 17,0 IP 54 215,5 112,5 带通风器 1,5 右转 2300 4,0 14,0 IP23 158,5 80,0 带热保护 0,8 可换向 3500 4,0 9,0 IP44 173,5 114,0 - 1,6 右转 2600 3,0 7,5 IP 54 207,5 131,0 带热保护 2,4 右转 2600 1,0 8,0 IP 54 183,0 114,0 - 1,5 右转 2300 2,0 8,0 IP 54	(mm) (mm) (kW) (cpm) (cmin) (cmin)

附件	
HK K REL	直流电动机的启动继电器
HK K CAP	直流电动机的防护盖